



ARCAN 1

Mobil Industrial , Canada

Water Resistant Filler Type Grease

Product Description

Arcan 1 lubricant is a white colored filler type grease which is readily dispensed by hand or power-operated grease guns. Arcan 1 grease is widely used in bearings and mechanisms to combat severe water contamination. Arcan 1 grease has good adhesion to metal under wet conditions and maintains a lubricating film and stays in place to protect metal surfaces from corrosion for extended intervals. Arcan 1 grease has an operating range of - 5°C to 110°C.

Because of the properties referred to above, Arcan 1 grease finds use in many applications such as printing machines, laundry and dry cleaning equipment, lubrication of office equipment and many other similar installations.

Arcan 1 grease is not recommended for wheel bearings, electric motor bearings, or other high speed, grease packed anti-friction bearings because of the presence of a filler.

Typical Properties

	Arcan 1
Soap Type Lithium	
Worked Penetration @ 25°C	310
Base Oil Viscosity, cSt	
@ 40°C	100
@ 100°C	10
Dropping Point °C	185

The values shown above are representative of current production. Some are controlled by manufacturing and performance specifications while others are not. All may vary within modest ranges.

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended applications and the recommendations provided in the Material Safety Data Sheet. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype and the Pegasus design are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

09-2019

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M

Calgary AB T2P 3 M 9

1-800-268-3183


Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is

intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved