



Mobil 1™ 0W-30

Mobil Passenger Vehicle Lube , Canada
Advanced Fuel Economy, Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ 0W-30 is an advanced full synthetic motor oil designed to help deliver outstanding engine protection to keep your engine running like new and protect engine parts for up to 16,000 kilometers between oil changes*. Mobil 1 0W-30 meets or exceeds the requirements of the industry's toughest standards and outperforms our conventional and synthetic blend oils. Mobil 1™ synthetic motor oil technology comes as standard equipment in many different vehicles, including high-performance vehicles.

Features and Benefits

Mobil 1™ 0W-30 is engineered with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced additive system. The advanced synthetic formulation helps to increase engine efficiency, while providing outstanding overall engine protection.

Key features and potential benefits include:

Features	Advantages and Potential Benefits
Advanced full synthetic formula	Keeps your engine running like new
Outstanding thermal and oxidation stability	Protects for up to 16,000 kilometers between oil changes*
Outstanding low temperature capabilities	Quick cold weather starting and fast protection helps to extend engine life
Active cleaning agents	Can clean up sludge left behind in your engine
Precisely balanced additive component system	Excellent wear protection

Applications

Mobil 1™ 0W-30 is recommended by Imperial Oil for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged multi-valve fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

- Mobil 1 0W-30 is recommended for SAE 0W-30, 5W-30 and 10W-30 applications.
- Mobil 1 0W-30 is recommended for extreme cold conditions to help deliver quick starts and fast lubrication.
- Mobil 1 0W-30 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

*Protection for up to 16,000 kilometers or 1 year, whichever comes first. To learn more about the Mobil 1 Limited Warranty, visit mobil1.ca.

Specifications and Approvals

This product has the following approvals:
GM Dexos1 Gen3

This product is recommended for use in applications requiring:

FORD WSS-M2C953-A

Ford

This product meets or exceeds the requirements of:

ILSAC GF-6A

FORD WSS-M2C963-A1

API SJ

API SL

API SM

API SN

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SN Resource Conserving

API SP

API SP Resource Conserving

Properties and Specifications

Property	
Grade	SAE 0W-30
Pour Point, °C, ASTM D97	-54
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	56
Flash Point, Cleveland Open Cup, °C, ASTM D92	227
Density @ 15.6 C, g/ml, ASTM D4052	0.8424

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023

Imperial Oil

Petroleum and Chemicals Division
Lubricants and Specialties
240 Fourth Ave SW
C. P. 2480, Station M
Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com. ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved