



Mobil ATF 3309

Mobil Passenger Vehicle Lube , Canada

Automatic Transmission Fluid

Product Description

Mobil ATF™ 3309 is a high performance lubricant that meets original equipment manufacturers' specifications for use in certain slip-controlled lock-up aut transmissions.

Features and Benefits

The unique formulation of Mobil ATF 3309 is designed to provide excellent lubrication of transmissions in specified slip-controlled lock-up automatic transmissions. outstanding performance capabilities translate into significant operational benefits, including:

- Excellent lubricating characteristics for quiet operation and smooth shifting in approved transmissions
- Controlled friction properties for smooth and efficient transmission of power across all normal temperature ranges
- Helps to control transmission shudder and provide excellent vehicle driveability
- Helps to extend transmission life based on excellent wear control
- Long fluid life based on excellent oxidation resistance
- Excellent viscosity stability (high viscosity index) to help assure adequate lubrication without excessive thinning in severe high-temperature service or thickening starting temperatures
- Resistance to foaming
- Superb protection against rusting and corrosion
- Compatibility with synthetic rubber seal materials

Applications

Mobil ATF 3309 is recommended for use in transmissions requiring fluids of JWS 3309 or GM 9986195 quality levels. It is also recommended for service fill applic where Toyota T-IV is requiried. Please refer to the owners' manual for proper fluid requirements.

Specifications and Approvals

This product is recommended for use in applications requiring:
AUDI G-055-025-A2
GM 9986195
TOYOTA T-IV

This product meets or exceeds the requirements of:
FORD WSS-M2C924-A

Properties and Specifications

Property	
Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983	13000

Property	
Color, Visual	Red
Density @ 15 C, g/cm3, ASTM D4052	0.852
Flash Point, Cleveland Open Cup, °C, ASTM D92	198
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	7.1
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	33
Viscosity Index, ASTM D2270	181

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

Imperial Oil

Petroleum and Chemicals Division  
Lubricants and Specialties  
240 Fourth Ave SW  
C. P. 2480, Station M  
Calgary AB T2P 3 M 9  
1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved