



Mobil Super™ 2000 Series

Mobil Passenger Vehicle Lube , Canada  
Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super™ 2000 uses a combination of synthetic and conventional high quality base oils combined with modern performance additives to help provide long life and outstanding protection for vehicles with more than 120,000 kilometres. Formulated with seal conditioner, Mobil Super 2000 helps prevent leaks and red consumption.

These oils protect against sludge, engine rust and corrosion under severe and low-temperature operating conditions. Pour point depressants and a viscosity improver are included to provide the optimum viscosity and fluidity across a broad range of temperatures.

Mobil Super 2000 oils are available in three multi-viscosity grades: SAE 5W-20, 5W-30 and 10W-30.

Mobil Super 2000 5W-20, 5W-30 and 10W-30 contain friction-reducing additives. All three products meet or exceed ILSAC GF-5 and API SN and are backward compatible with earlier performance levels such as API SM, SL, and SJ. The American Petroleum Institute (API) classifies these three products as "Resource Conserving" engine lubricants.

Features and Benefits

\*\*The extended performance and guaranteed protection applies to vehicles recommending oil drain intervals 10,000 km or less. Excludes severe service applications involving: racing and commercial use; frequent towing or hauling; extremely dusty or dirty conditions; or excessive idling. While under warranty change oil at manufacturer's recommended interval.

- Helps extend engine life
- Contains seal conditioner to help prevent or control leaks and reduce oil consumption
- Protects older engines
- Extended performance, guaranteed protection to 10,000 kilometres oil drain interval\*\*
- Outstanding wear protection under a wide variety of operating conditions
- Easy cold starting.
- Meets or exceeds the latest industry specifications
- Satisfies the latest fuel efficiency requirements

Applications

Mobil Super 2000 5W-20, 5W-30 and 10W-30 are recommended for higher mileage (generally more than 120,000 kilometres) gasoline, propane or E-85 fueled and light duty trucks requiring an API SN, SM, SL or SJ product. They also meet the requirements of ILSAC GF-5 (Starburst Certification Symbol).

Before using a Mobil Super 2000 motor oil, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product is recommended for use in applications requiring:	5W-20	5W-30	10W-30
Fiat Chrysler Automotive MS-6395	X	X	
Ford WSS-M2C929-A		X	

This product is recommended for use in applications requiring:	5W-20	5W-30	10W-30
Ford WSS-M2C930-A	X		
GM 6094M			X

This product meets or exceeds the requirements of:	5W-20	5W-30	10W-30
API SJ	X	X	X
API SL	X	X	X
API SM	X	X	X
API SN	X	X	X
API SN PLUS	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X
API SN Resource Conserving	X	X	X
Ford WSS-M2C945-A	X		
Ford WSS-M2C945-B1	X		
Ford WSS-M2C946-A		X	
Ford WSS-M2C946-B1		X	

## Properties and Specifications

Property	5W-20	5W-30	10W-30
Grade	SAE 5W-20	SAE 5W-30	SAE 10W-30
ASTM Color, ASTM D1500	3	3	3
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293			3800 max
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	6600 max	6600 max	
Density @ 15.6 C, g/ml, ASTM D4052	0.8586	0.8591	0.8612
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	8.3	10.3	10.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	49	63	65

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2021

**Imperial Oil**

Petroleum and Chemicals Division  
Lubricants and Specialties  
240 Fourth Ave SW

C. P. 2480, Station M  
Calgary AB T2P 3 M 9  
1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved