



Mobil 1™ 5W-30

Mobil Passenger Vehicle Lube , Canada

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ 5W-30 is an advanced full synthetic motor oil designed to help deliver outstanding engine protection to keep your engine running like new and protect critical engine parts for up to 16,000 kilometers between oil changes*. Mobil 1 5W-30 meets or exceeds the industry's toughest standards and outperforms our conventional and synthetic blend oils. Mobil 1™ synthetic motor oil technology comes as standard equipment in many different vehicles, including select high-performance vehicles.

Features and Benefits

Mobil 1™ 5W-30 is made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced additive system. Mobil 1 5W-30 is designed to provide outstanding overall engine protection to keep your engine running like new, while meeting or exceeding the latest industry performance standards.

Key features and potential benefits include:

| Features | Advantages and Potential Benefits |
|--|---|
| Advanced full synthetic formula | Keeps your engine running like new |
| Outstanding thermal and oxidation stability | Protects for up to 16,000 kilometers between oil changes* |
| Excellent low temperature capabilities | Quick cold weather starting and fast protection helps to extend engine life |
| Active cleaning agents | Can clean up sludge left behind in your engine |
| Precisely balanced additive component system | Excellent wear protection |

Applications

Mobil 1™ 5W-30 is recommended for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

- Mobil 1 5W-30 is a high-performance motor oil for all types of cars where this viscosity is recommended.
- Mobil 1 5W-30 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

*Protection for up to 16,000 kilometers or 1 year, whichever comes first. To learn more about the Mobil 1 Limited Warranty, visit mobil1.ca.

Specifications and Approvals

| |
|--|
| This product has the following approvals: |
| GM dexos1:GEN3 Licensed |

This product has the following approvals:

HONDA/ACURA HTO-06

This product is recommended for use in applications requiring:

Ford WSS-M2C946-A

GM 4718M

GM 6094M

Ford WSS-M2C929-A

Ford WSS-M2C946-B1

This product meets or exceeds the requirements of:

API SN

API SM

API SL

API SJ

API SN Resource Conserving

API SN PLUS

API SN PLUS RESOURCE CONSERVING

API SP

API SP Resource Conserving

ILSAC GF-6A

FORD WSS-M2C961-A1

Chrysler MS-6395

CHRYSLER MS-13340

Properties and Specifications

| Property | |
|---|-----------|
| Grade | SAE 5W-30 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.8478 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 242 |

| Property | |
|--|-------|
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 10.75 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 62.17 |
| Pour Point, °C, ASTM D97 | -42 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2022

Imperial Oil

Petroleum and Chemicals Division
Lubricants and Specialties
240 Fourth Ave SW
C. P. 2480, Station M
Calgary AB T2P 3 M 9
1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved