



Mobil Super 1000

Mobil Passenger Vehicle Lube , Canada

Synthetic Blend Motor Oil

Product Description

Mobil Super™ 1000 oils are formulated from quality base stocks combined with modern performance additives to give your engine the protection it requires and the performance you expect from your vehicle under a wide variety of operating conditions.

Mobil Super 1000 oils are available in three multi-viscosity grades: SAE 5W-20, 5W-30 and 10W-30.

Mobil Super 1000 5W-20, 5W-30 and 10W-30 meet the warranty requirements where an American Petroleum Institute (API) certified oil is specified. All three products meet or exceed ILSAC GF-5 and API SN Plus and are backward compatible with earlier performance levels such as API SN, SM, SL, and SJ. The American Petroleum Institute (API) classifies these three products as "Resource Conserving" engine lubricants.

Features and Benefits

- Helps keep engines clean
- Helps fuel efficiency
- Helps reduce engine wear and corrosion
- Meets or exceeds the latest industry specification (ILSAC GF-5 / API SN Plus Resource Conserving)
- Easy cold starting

Applications

•Mobil Super 1000 5W-20, 5W-30 and 10W-30 are recommended for gasoline, propane and E-85 fueled cars and light duty trucks where an oil meeting API SN Plus, SN, SM, SL or SJ is required. They meet ILSAC GF-5 (Starburst Certification Symbol).

•Before using a Mobil Super 1000 motor oils, consult the owner's manual of the vehicle for the manufacturer's recommended viscosity grade and API Service Classification.

Specifications and Approvals

This product is recommended for use in applications requiring:	5W-20	5W-30	10W-30
Fiat Chrysler Automotive MS-6395		X	X
Ford WSS-M2C929-A		X	
GM 6094M	X	X	

This product meets or exceeds the requirements of:	5W-20	5W-30	10W-30
API SL	X		
API SM	X		

This product meets or exceeds the requirements of:	5W-20	5W-30	10W-30
API SN	X		
API SN PLUS	X	X	X
API SN PLUS RESOURCE CONSERVING	X	X	X
API SN Resource Conserving	X		
ILSAC GF-5	X		
Ford WSS-M2C930-A	X		
Ford WSS-M2C945-A	X		
Ford WSS-M2C945-B1	X		
Ford WSS-M2C946-A		X	
Ford WSS-M2C946-B1		X	

Properties and Specifications

Property	5W-20	5W-30	10W-30
Grade	SAE 5W-20	SAE 5W-30	SAE 10W-30
ASTM Color, ASTM D1500	3	1.5	2
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293			5500 max
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	6600 max	6600 max	
Density @ 15.6 C, g/ml, ASTM D4052	0.8586	0.858	0.8665
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.3	10.7	10.7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	48.8	64	73

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2021

Imperial Oil

Petroleum and Chemicals Division

Lubricants and Specialties

240 Fourth Ave SW

C. P. 2480, Station M


Calgary AB T2P 3 M 9

1-800-268-3183

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect

product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local Imperial Oil contact or visit www.imperialoil.ca ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Imperial Oil, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved