



Mobilube™ GX-A 80W

Mobil Commercial Vehicle Lube , Rep.of Congo

Automotive Gear Lubricant

Product Description

Mobilube GX-A 80W is an automotive gear lubricant formulated from high performance base oils and an advanced additive system. This lubricant is engineered for commercial transmissions, axles, and final drives where protection against wear and scoring is required. It is recommended by ExxonMobil for use in Mercedes Benz applications where MB-Approval 235.1 is required and in applications where API GL-4 service is required.

Features and Benefits

Today's drivetrain applications place higher performance demands on lubricants. Higher speeds, higher torque, and heavier loads require improved formulations to maximise equipment life and optimise operating costs. Longer service intervals place additional demands on the gear lubricant requiring effective basestock and additive systems. Mobilube GX-A 80W is engineered to meet these challenges. The key benefits include:

Features	Advantages and Potential Benefits
Good thermal stability and resistance to high temperature oxidation	Long gear and bearing life due to minimal deposits Long seal life
Excellent rust and corrosion protection	Long component life
Good low temperature lubrication	Reduced wear at start-up and ease of start-up
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination

Applications

Recommended by ExxonMobil for use in:

- Manual transmissions and drive axles requiring API GL-4 level performance
- Passenger cars, onhighway light and heavy-duty trucks and commercial vehicles
- Off-highway industries including: construction, quarrying, and agriculture
- Other industrial, commercial, and automotive applications including hypoid gears operating under moderate to severe operating conditions

Specifications and Approvals

This product has the following approvals:
DTFR 13B100
ZF TE-ML 17A
MB 235.14

This product is recommended for use in applications requiring:
API GL-4

This product is recommended for use in applications requiring:

MAN 341 Typ Z1

This product meets or exceeds the requirements of:

R. Bosch AS TE-ML 08

Properties and Specifications

Property	
Grade	SAE 80W
Density @ 15 C, kg/l, ASTM D4052	0.89
Flash Point, Cleveland Open Cup, °C, ASTM D92	216
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.0
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	76
Pour Point, °C, ASTM D97	-30
Viscosity Index, ASTM D2270	104

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2024

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved