



## Mobil Vactra™ Oil Numbered Series

Mobil Industrial , Rep.of Congo

Way and Slide Lubricants

### Product Description

The Mobil Vactra™ Oil Numbered Series are premium-quality slideway lubricants specifically designed to meet the requirements for accuracy, aqueous coolant separability, and equipment protection of precision machine tools.

The Mobil Vactra Oil Numbered Series is carefully formulated from high-quality base stocks and performance balanced with an advanced additive system that provides controlled frictional properties, compatibility with aqueous metal working fluids and corrosion protection of parts and equipment. The unique additive package provides exceptional frictional properties on a wide variety of way materials, including steel on steel and steel on polymer, reducing stick-slip and chatter. This allows smooth, uniform motion at design travel speeds enhancing machine productivity and accuracy helping to prolong tool life and enhance surface finish. The Mobil Vactra Oil Numbered Series has been optimized to provide separability from many aqueous coolants while minimizing the corrosive effects of high pH coolants on lubricated surfaces.

### Features and Benefits

The Mobil Vactra Oil Numbered Series has been developed and specifically designed to provide an extra margin of machinery protection by satisfying the stringent demands of slide ways. The oils exhibit excellent lubricity and load-carrying performance contributing significantly to improving the production of quality parts. The Mobil Vactra Oil Numbered Series provides separability from many water and aqueous coolants reducing the potential negative effects of cross contamination which helps to enhance the service life and performance of both the lubricant and coolant.

Features	Advantages and Potential Benefits
Controlled Frictional Characteristics	Helps eliminate stick slip; allows consistently accurate machining
Multi-material Capabilities	Suitable for a wide range of way material combinations allowing for product consolidation
Water and Aqueous Coolant Separability	Helps improve the life and performance of many aqueous coolants
Adhesiveness	Prevents removal of lubricant from critical surfaces
Long Term Rust and Corrosion Protection	Helps reduce the deterioration of sliding surfaces in the presence of water and aqueous coolants

### Applications

Mobil Vactra Oil Numbered Series products are recommended for the lubrication of machine tool slideway systems. They are designed for use with combinations of cast iron, steel and non-metallic way materials. Mobil Vactra Oil Numbered Series may be applied by hand, forced-feed lubricator or in flood application by circulation system.

- Mobil Vactra Oil No. Series of products are suitable for use in applications that require Fives Cincinnati specifications P53, P47, and P50.
- Mobil Vactra Oil No. 1 and No. 2 are recommended for horizontal slideways on small to medium size machine tools. They are also suitable for circulating application in large machines and as a moderate duty hydraulic fluid.
- Mobil Vactra Oil No. 3 and No. 4 are normally recommended for large machines where way pressures are high and good precision is required. They are also recommended for vertical and inclined slideways where drain-down can be a problem and for moderate service machine tool gear drive mechanisms.
- Mobil Vactra Oil Numbered Series can be used for lubrication of ball screws, linear guides, headstocks, translating screws.
- Mobil Vactra Oil Numbered Series is recommended for applications where oil contamination of the aqueous coolants shortens coolant batch life.

## Specifications and Approvals

This product is recommended for use in applications requiring:	NO. 1	NO. 2	NO. 3	NO. 4
Fives Cincinnati P-47		X		
Fives Cincinnati P-50				X
Fives Cincinnati P-53	X			

This product meets or exceeds the requirements of:	NO. 1	NO. 2	NO. 3	NO. 4
DIN 51502 CGLP	X	X	X	X
ISO L-GA (ISO 6743-13:2002)		X	X	X
ISO L-GB (ISO 6743-13:2002)		X	X	X

## Properties and Specifications

Property	NO. 1	NO. 2	NO. 3	NO. 4
Grade	ISO 32	ISO 68	ISO 150	ISO 220
Copper Strip Corrosion, 3 h, 100 C, Rating, ASTM D130	1B	1B	1B	1B
FZG Scuffing, Fail Load Stage, A/8.3/90, ISO 14635-1	13	13	13	13
Flash Point, Cleveland Open Cup, °C, ASTM D92	216	228	248	240
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	32	68	156	221
Pour Point, °C, ASTM D97	-30	-9	-6	-6

## Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2024

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved