



## Mobil ATF™ 134

Mobil Passenger Vehicle Lube , Switzerland

Automatic Transmission Fluid

### Product Description

Mobil ATF 134 is an extra high performance automatic transmission fluid formulated with selected HVI base oils and recommended for use in Mercedes automatic gearboxes.

### Features and Benefits

Mobil ATF 134 is formulated with an advanced additive system in combination with a carefully selected composition of HVI base oils providing excellent thermal stability and wear resistance as well as very good low temperature properties. Key features and benefits include:

Features	Advantages and Potential Benefits
Excellent low-temperature pumpability and circulation	Gives outstanding cold start performance
Enhanced anti-wear properties	Improves wear protection and longer transmission life
Formulated to meet latest frictional requirements	Gives smooth transmission operation during the entire service time
Excellent protection against degradation at high operating temperatures	For extended service life

### Applications

Mobil ATF 134 is recommended for use in the latest generation of Mercedes Benz 7-speed automatic transmission gearboxes. It is approved against MB 236.14.

### Specifications and Approvals

<b>This product has the following approvals:</b>
MB-Approval 236.14

### Properties and Specifications

Property	
Colour, DIN ISO 2549	Red
Flash Point, Cleveland Open Cup, °C, EN ISO 2592	200
Kinematic Viscosity at 100 C, mm <sup>2</sup> /s, DIN 51562-1	6,5
Kinematic Viscosity at 40 C, mm <sup>2</sup> /s, DIN 51562-1	29,6
Pour Point, C, DIN ISO 3016	-51

Property	
Viscosity Brookfield at -40C, cP, DIN 51398	8500
Viscosity Index, DIN 2909	185

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

EXXONMOBIL LUBRICANTS & SPECIALTIES EUROPE, A DIVISION OF EXXONMOBIL PETROLEUM & CHEMICAL, BVBA (EMPC)

POLDERDIJKWEG

B-2030 Antwerpen


Belgium

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved