



Mobil Delvac Elite 15W-40

Mobil Commercial Vehicle Lube , Chile

Premium Synthetic Blend Diesel Engine Oil

Product Description

Mobil Delvac Elite 15W-40 is a premium synthetic blend heavy duty diesel engine oil for long drain capability that meets the CJ-4 specification, providing the highest level of protection in severe on and off highway applications, high performance diesel engines with Exhaust Gas Recirculation (EGR) and Aftertreatment Systems with Diesel Particulate Filters (DPFs) and Diesel Oxidation Catalysts (DOCs).

Fully backward compatible, Mobil Delvac Elite 15W-40 is approved by major original equipment manufacturers (OEM).

Features and Benefits

Mobil Delvac Elite 15W-40 exhibit outstanding low temperature fluidity, high temperature viscosity retention, and piston deposit control.

Applications

- Recommended for the latest heavy duty diesel engines, including those equipped with aftertreatment systems and EGR.
- Recommended for diesel applications using older and naturally aspirated conventional designs.
- High performance gasoline engines requiring API SM and mixed fleet operations.

Specifications and Approvals

This product has the following approvals:
Mack EO-N Premium Plus 03
Mack EO-O Premium Plus
VOLVO VDS-3
VOLVO VDS-4

This product is recommended for use in applications requiring:
API CF
API CG-4

This product meets or exceeds the requirements of:
API CH-4
API CI-4
API CI-4 PLUS
API CJ-4

This product meets or exceeds the requirements of:

API SL

API SM

Caterpillar ECF-2

Caterpillar ECF-3

RENAULT TRUCKS RLD-3

Properties and Specifications

Property	
Grade	SAE 15W-40
Total Base Number, mgKOH/g, ASTM D4739	8.6
Pour Point, °C, ASTM D97	-27
Density @ 15 C, kg/l, ASTM D4052	0.87
Viscosity Index, ASTM D2270	137
Flash Point, Cleveland Open Cup, °C, ASTM D92	231
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.7
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	111

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved