



Mobil 1™ Extended Performance

Mobil Passenger Vehicle Lube , Chile

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ Extended Performance oils are advanced full synthetic motor oils designed to deliver outstanding engine protection and protect critical engine parts for 20,000 miles between oil changes*. Mobil 1 Extended Performance meets or exceeds the industry's toughest standards and is especially formulated to protect longer oil change intervals. Mobil 1™, synthetic motor oil technology, comes as standard equipment in many different vehicles, including select high-performance vehicles.

Features and Benefits

Mobil 1™ Extended Performance motor oils are made with a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced complete additive system to meet or exceed industry's toughest performance standards. Mobil 1 Extended Performance oils are designed to provide outstanding levels of engine protection, even during longer oil change intervals.

Key features and potential benefits include:

| Features | Advantages and Potential Benefits |
|---|--|
| Advanced full synthetic formula | Exceptional overall engine protection |
| Precise balance of performance additives | Unsurpassed wear protection |
| Outstanding thermal and oxidation stability | Protects for up to 20,000 miles between oil changes* |
| Active cleaning agents | Designed to clean up sludge left behind in your engine |
| Excellent low temperature capabilities | Quick cold weather starting down to -40°C for fast protection and extended engine life |

Applications

Mobil 1™ Extended Performance motor oils are recommended by ExxonMobil for all types of modern gasoline-powered vehicles, including high-performance turbocharged, supercharged, multi-valve fuel injected engines found in passenger cars, SUVs, light vans and trucks.

- Mobil 1 Extended Performance motor oils provide guaranteed protection of critical engine parts for up to 20,000 miles or one year, whichever comes first. Excludes severe service includes: commercial and racing applications; frequent towing or hauling; extremely dusty or dirty conditions; or excessive idling.
- If your vehicle is covered by a warranty, follow the vehicle's oil life sensor or the oil change interval recommended in your owner's manual. Proper maintenance practices, including frequently checking the oil level to ensure that the appropriate amount of oil is present, are required to ensure effective performance.
- Mobil 1 Extended Performance oils are not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Always check your owner's manual for the manufacturer's recommended oil viscosity grade, API service classification and any builder approval.

Specifications and Approvals

| This product has the following approvals: | 0W-20 | 5W-20 | 5W-30 | 10W-30 |
|---|-------|-------|-------|--------|
| HONDA/ACURA HTO-06 | | | X | |

| This product is recommended for use in applications requiring: | 0W-20 | 5W-20 | 5W-30 | 10W-30 |
|--|-------|-------|-------|--------|
|--|-------|-------|-------|--------|

| This product is recommended for use in applications requiring: | 0W-20 | 5W-20 | 5W-30 | 10W-30 |
|--|-------|-------|-------|--------|
| Ford WSS-M2C945-A | | X | | |
| Ford WSS-M2C945-B1 | | X | | |
| Ford WSS-M2C946-A | | | X | |
| FORD WSS-M2C946-B1 | | | X | |
| Ford WSS-M2C947-A | X | | | |
| FORD WSS-M2C947-B1 | X | | | |
| FORD WSS-M2C960-A1 | | X | | |
| FORD WSS-M2C962-A1 | X | | | |
| Fiat Chrysler Automotive MS-6395 | X | X | | |
| API CF | X | X | X | |
| Ford WSS-M2C929-A | | | X | |
| Ford WSS-M2C930-A | | X | | |
| GM 4718M | | | X | X |
| GM 6094M | X | X | X | X |

| This product meets or exceeds the requirements of: | 0W-20 | 5W-20 | 5W-30 | 10W-30 |
|--|-------|-------|-------|--------|
| API SJ | X | X | X | X |
| API SL | X | X | X | X |
| API SM | X | X | X | X |
| API SN | X | X | X | X |
| API SN PLUS | X | X | X | X |
| API SN PLUS RESOURCE CONSERVING | X | X | X | X |
| API SN Resource Conserving | X | X | X | X |
| API SP | X | X | X | X |
| API SP Resource Conserving | X | X | X | X |
| ILSAC GF-6A | X | X | X | X |
| ACEA A5/B5 | | | X | X |
| FORD WSS-M2C961-A1 | | | X | |

Properties and Specifications

| Property | 0W-20 | 5W-20 | 5W-30 | 10W-30 |
|----------|-------|-------|-------|--------|
|----------|-------|-------|-------|--------|

| Property | 0W-20 | 5W-20 | 5W-30 | 10W-30 |
|---|-----------|-----------|-----------|------------|
| Grade | SAE 0W-20 | SAE 5W-20 | SAE 5W-30 | SAE 10W-30 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.839 | | | |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 235 | 230 | 230 | 232 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 8.6 | 9 | 10.6 | 10.2 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | | | | |
| Pour Point, °C, ASTM D97 | -54 | -42 | -40 | -39 |

*Protects for up to 20,000 miles or 1 year, whichever comes first. To learn more about the Mobil 1 Limited Warranty, visit Mobil.US.

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2024
COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTD

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved