



MOBIL SUPER 1000 X3 15W40

Mobil Passenger Vehicle Lube , Chile

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super 1000 X3 15W-40 is a premium quality mineral motor oils meeting the latest industry engine oil specifications. It is designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Mobil Super 1000 X3 15W-40 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and helps promote long engine life.

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super 1000 X3 15W-40 has been formulated to be suitable for use in nearly all vehicles. ExxonMobil particularly recommend Mobil Super 1000 X3 15W-40 for daily driving under normal conditions:

- Nearly all gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
API CD
API CF
API SG

This product meets or exceeds the requirements of:
API SJ
API SL
API SM

Properties and Specifications

Property	
Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-39
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Density @ 15.6 C, g/ml, ASTM D4052	0.88
Ash, Sulfated, mass%, ASTM D874	0.97
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.5
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	109

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2020

Compañía de Petróleos de Chile Copec SA

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved