



Mobil Super™ 1000 X1 10W-30

Mobil Passenger Vehicle Lube , Chile

Product Description

Mobil Super™ 1000 X1 10W-30 is a premium quality mineral motor oil meeting the industry engine oil specifications. Designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Engine protection during start up

Extended protection against engine wear and deposits formation

Helps combat sludge

Mobil Super™ 1000 X1 10W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and helps promote long engine life.

Applications

ExxonMobil particularly recommend Mobil Super™ 1000 X1 10W-30 for daily driving under normal conditions:

- Nearly all gasoline engine technologies
- Passenger cars, SUV's, light trucks and vans
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:

ILSAC GF-4

This product meets or exceeds the requirements of:

API SL

API SM

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 10W-30 |
| Specific Gravity, 15.6 C/15.6 C, ASTM D4052 | 0.88 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 222 |
| Pour Point, °C, ASTM D97 | -33 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 10.3 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 67.8 |
| Viscosity Index, ASTM D2270 | 139 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2021

COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil Esso XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved