



Mobil Super™ 3000 5W-30

Mobil Passenger Vehicle Lube , Chile

Mobil passenger-vehicle-lube

Product Description

Mobil Super™ 3000 5W-30 is a full synthetic engine oil is tailored for smoother acceleration and provides outstanding engine wear protection even under the most demanding driving conditions.

Mobil Super™ 3000 5W-30 provides superior engine protection under high temperature, is proven during API SP engines test in reduces damaging Low Speed Pre-Ignition (LSPI) problem is modern engines. This helps to improve engine efficiencies and prolong engine life.

Features and Benefits

- Suitable for Toyota, Honda, Nissan, Hybrid and other newer Japanese gasoline engines
- Provides high temperature wear protection while keeping your engine clean
- Better engine wear protection up to 65%*
- Improve engine efficiencies by reducing Engine Low Speed Pre-Ignition (LSPI)

*Based on Sequence IWB (Iron Wear) test result versus API SP engine test requirement. Result varies subject to engine, temperature and actual driving conditions.

Applications

Mobil Super™ 3000 5W-30 exceeds the latest API SP gasoline engine oil test specification and can be use in cars that requires API SN PLUS/SN/SM/SL specifications. It is also recommended for diesel engine application requiring 5W-30 viscosity.

Specifications and Approvals

This product is recommended for use in applications requiring:

Ford WSS-M2C929-A

Ford WSS-M2C946-A

Ford WSS-M2C946-B1

GM 6094M

This product meets or exceeds the requirements of:

API SJ

This product meets or exceeds the requirements of:
API SL
API SM
API SN
API SN PLUS
API SN PLUS RESOURCE CONSERVING
API SN Resource Conserving
API SP
API SP Resource Conserving
ILSAC GF-6A
Chrysler MS-6395
FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Density @ 15 C, g/ml, ASTM D4052	0.85
Flash Point, Cleveland Open Cup, °C, ASTM D92	232
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.1
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	10.6
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	61.2
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	18300
Viscosity Index, ASTM D2270	163
Total Base Number, mgKOH/g, ASTM D2896	7.2
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2021

Compañía de Petróleos de Chile Copec SA

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil  

© Copyright 2003–2019 Exxon Mobil Corporation. All Rights Reserved