



Mobil Super™ 3000 Formula V 5W-30

Mobil Passenger Vehicle Lube , Chile

High Performance Motor Oil

Product Description

Mobil Super 3000 Formula V 5W-30 is a low ash high performance motor oil designed to meet the demanding requirements of extended service life whilst still contributing towards fuel economy and superior engine cleanliness.

Features and Benefits

Mobil Super 3000 Formula V 5W-30 delivers excellent high and low temperature wear-protection and improved engine cleanliness.

Key features and benefits:

- Extended service interval as per VW requirements.
- Helping achieve fuel economy (as per ACEA C3).
- Improved engine internal cleanliness to maintain engine efficiency over life of vehicle.
- Fast circulation and protection.
- Full compatibility with most Diesel Particulate Filters and Catalytic Convertors.

Applications

Mobil Super 3000 Formula V 5W-30 has been designed to meet the needs of the latest engine requirements of the VW Audi group where extended drain is required in conjunction with electronic service indicators with VW extended drain service schedule.

Specifications and Approvals

This product has the following approvals:
VW 507 00
VW 504 00
MB-Approval 229.51
MB-Approval 229.31
BMW Longlife 04

This product meets or exceeds the requirements of:
API SN
ACEA C3

Properties and Specifications

Property	
-----------------	--

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	66
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	11.7
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Density @ 15 C, g/ml, ASTM D1298	0.852
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2023

COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved