



Mobil Super™ Moto 2T

Mobil Passenger Vehicle Lube , Chile

High Performance Two-Stroke Engine Oil

Product Description

Mobil Super Moto 2T is a high performance oil used for lubrication of motorcycles and other equipment using two-stroke petrol engines with automatic lubrication system or oil/fuel mixture. Mobil Super Moto 2T is pre-diluted to ensure rapid mixing when added to fuel. Use the mixing ratio recommended by the manufacturer. Always follow the owner's manual recommendations.

Features and Benefits

Mobil Super Moto 2T combines high quality mineral oils with a strong additive system to provide good overall cleaning and performance. Key features and benefits include:

Features	Advantages and Potential Benefits
Good wear protection	Helps provide longer engine life
Thermal and oxidation stability and deposit control	Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking and piston tightening as well as protection against pre-ignition problems
Good corrosion protection properties	Helps provide longer engine life
Reduces pre-ignition	Improved fuel efficiency and extended piston life

Specifications and Approvals

This product meets or exceeds the requirements of the following industry specification:
API TC
ISO-L-EGB
JASO FB
SAE GRADE 1

Properties and Specifications

Property	
Ash, Sulfated, mass%, ASTM D874	0.09
Density @ 15 C, g/ml, ASTM D4052	0.877
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	88.5
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.5

Property	
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	59.2
Pour Point, °C, ASTM D97	-9
Viscosity Index, ASTM D2270	115

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023


COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003–2024 Exxon Mobil Corporation. All Rights Reserved