



## Mobil Super™ Moto 2T

Mobil Passenger Vehicle Lube , Chile

High Performance Two-Stroke Engine Oil

### Product Description

Mobil Super Moto 2T is a high performance oil used for lubrication of motorcycles and other equipment using two-stroke petrol engines with automatic lubrication system or oil/fuel mixture. Mobil Super Moto 2T is pre-diluted to ensure rapid mixing when added to fuel. Use the mixing ratio recommended by the manufacturer. Always follow the owner's manual recommendations.

### Features and Benefits

Mobil Super Moto 2T combines high quality mineral oils with a strong additive system to provide good overall cleaning and performance. Key features and benefits include:

| Features  | Advantages and Potential Benefits  |
|---|--|
| Good wear protection                                | Helps provide longer engine life   |
| Thermal and oxidation stability and deposit control | Cleaner engines resulting in extended spark plug and valve life, reduced ring sticking and piston tightening as well as protection against pre-ignition problems |
| Good corrosion protection properties                | Helps provide longer engine life   |
| Reduces pre-ignition                                | Improved fuel efficiency and extended piston life  |

### Specifications and Approvals

| This product meets or exceeds the requirements of the following industry specification: |
|---|
| API TC  |
| ISO-L-EGB   |
| JASO FB   |
| SAE GRADE 1   |

### Properties and Specifications

| Property   |       |
|--|-------|
| Ash, Sulfated, mass%, ASTM D874                            | 0.09  |
| Density @ 15 C, g/ml, ASTM D4052                           | 0.877 |
| Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93       | 88.5  |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 8.5   |

| Property  |      |
|---|------|
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445 | 59.2 |
| Pour Point, °C, ASTM D97                                  | -9   |
| Viscosity Index, ASTM D2270                               | 115  |

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved