



## Mobil Permazone™

Mobil Passenger Vehicle Lube , Chile

Antifreeze and Coolant

### Product Description

Mobil Permazone Antifreeze and Coolant is a conventional green colored antifreeze containing inhibitors providing protection from freezing, overheating, rust and corrosion when used as recommended. Mobil Permazone Antifreeze and Coolant features a universal low silicate formula for use in all conventional automobiles and light duty trucks and protects all cooling system metal surfaces, including aluminum.

When used in heavy-duty applications, the addition of a separate Supplemental Coolant Additive (SCA) is required.

### Features and Benefits

- Protects all cooling system metals.
- Protects against damaging rust and corrosion.
- Provides freeze-up protection to -34°F and boil-over protection to +265°F.
- Compatible with all conventional green antifreeze.

### Specifications and Approvals

Mobil Permazone Antifreeze and Coolant meets or exceeds the requirements of:

ASTM D 3306	X
ASTM D 4340	X
ASTM D 4985	X
CID AA52624	X
Caterpillar	X
Chrysler MS 7170	X
Cummins 90T8-4	X
Ford ESE-M97B-44-A	X
GM 1825M / 1899M	X
John Deere H24B1 , H24C1	X
Mack Truck	X
Navistar B1	X
TMC TP 302B	X
SAE J1034	X
SAE J1941	X

ASTM D 3306	X
Volvo/GM Heavy Truck	X

### Protection Table

Concentration	Protects from	
	Freezing Down to	Boiling Up to*
40	-24°C / -11°F	127°C / 261°F
50	-37°C / -34°F	129°C / 265°F
60	-52 °C / -62°F	132 °C / 270 °F

\*Using a 15 PSI Pressure Cap

### Chemical Properties

Property	ASTM Test Method	Typical Values
Specific Gravity (60/60°F)	D1122	1.120 – 1.130
Freezing Point, 50 Vol. %, °F	D3321 or D1177	-34°F
Boiling Point, 50 Vol. %, °F	D1120	226°F
pH, 50% Volume Solution	D1287	10.0 – 11.0
Reserve Alkalinity, mL	D1121	11.0 Min
Foam Test	D1881	150 ml. / 5sec., Max
Color	Visual	Green

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2023

COPEC S.A.

Isidora Goyenechea 2915, Las Condes, Santiago Chile

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExonMobil**

Exxon

Mobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved