



Mobil Delvac™ Advanced City Logistics 15W-40

Mobil Commercial Vehicle Lube , 中国

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ Advanced City Logistics 15W-40 is a high performance diesel engine oil that provides engine protection of diesel engines operating in intra-city and inter-city logistics applications, involving frequent start-stop service. Mobil Delvac™ Advanced City Logistics 15W-40 is recommended by ExxonMobil for use in a wide range of new light-duty commercial vehicles.

Features and Benefits

The technology in Mobil Delvac™ Advanced City Logistics 15W-40 delivers excellent performance in both modern diesel engines as well as older models. The key benefits include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers
- Commercial Diesel engines meeting GB IV Emission Standard without diesel particulate filter (DPF) as after treatment

Specifications and Approvals

Mobil Delvac™ Advanced City Logistics 15W-40 meets or exceeds the requirements of the following industry specifications:
API CH-4
Mobil Delvac™ Advanced City Logistics 15W-40 is recommended by ExxonMobil for use in applications requiring:
API CG-4/CF-4/CF/SJ
ACEA E2

Typical Properties

SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	108
cSt @ 100°C	14.7
Viscosity Index, ASTM D 2270	140
Sulfated Ash, wt%, ASTM D 874	1.0

SAE Grade	15W-40
Total Base # , mg KOH/g, ASTM D 2896	9
Pour Point, °C, ASTM D 97	-27
Flash Point, °C, ASTM D 92	227
Density @ 15°C kg/l, ASTM D 4052	0.880

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil™ logotype, the Pegasus design, Mobil Delvac™ and Mobil Delvac Super™ are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved