



Mobil Delvac Super™ C 15W-40/20W-50

Mobil Commercial Vehicle Lube , 中国

High Performance Diesel Engine Oils

Product Description

Mobil Delvac Super™ C 15W-40/20W-50 is a high performance diesel engine oil that provides proven protection to diesel engines operating in severe on and off-highway service applications. Mobil Delvac Super C 15W-40/20W-50 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, construction, and agricultural industries.

Features and Benefits

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Clean engines and long engine life
Stay-in-grade shear stability	Reduced oil consumption and effective wear protection

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: trucking, construction, quarrying, and agriculture

Specifications and Approvals

This product is recommended for use in applications requiring:	SAE 15W-40	SAE 20W-50
API CF		X
API CF-4	X	X
API SG		X
API SF		X

Properties and Specifications

Property	SAE 15W-40	SAE 20W-50
Grade	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	0.7	0.7

Property	SAE 15W-40	SAE 20W-50
Flash Point, Cleveland Open Cup, °C, ASTM D92	234	231
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	15	18.2
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	117	163
Pour Point, °C, ASTM D97	-30	-27
Total Base Number, mgKOH/g, ASTM D2896	6	6

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2021
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO ENERGY

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved