



MOBIL DELVAC LEGEND™ ANTIFREEZE -35°C HEAVY DUTY

Mobil Commercial Vehicle Lube , 中国

Mobil commercial-vehicle-lube

Product Description

Mobil Delvac Legend Antifreeze -35°C Heavy Duty is an extended life ethylene glycol antifreeze for heavy duty diesel, gasoline, and natural gas powered engines.

Features and Benefits

- Provides excellent Anti-boiling, Anti-freezing, and Anti-corrosion protection of Heavy Duty engines and cooling system components
- Uses organic additive technology (OAT) corrosion inhibitors along with molybdate and nitrite to provide extra protection to cylinder liners found in heavy duty applications.
- Free of amines, borates, nitrates, phosphates and silicates.
- Widely applicable to many heavy duty applications found in on-road & off-road, marine, farm, mining and construction equipment (check vehicle service manual for special coolant requirements)
- Also provides protection in light duty engines equipment (check vehicle service manual for special coolant requirements)
- Does not require an initial charge of supplemental coolant additives (SCAs).
- Compatible with other similarly formulated OAT engine coolants
- Pre-diluted with water and needs no further water addition

Applications

Mobil Delvac Legend Antifreeze -35°C Heavy Duty is formulated to be an extended life coolant in heavy duty applications found in on-road & off-road, marine, farm, mining and construction equipment. It also provides protection in light duty engines making it highly suitable for mixed fleets (light duty as well as heavy duty gasoline and diesel engines)*.

* Before using any coolant, please ensure that you have consulted your vehicle owner's manual and your vehicle manufacturer's recommendations prior to use.

Specifications and Approvals

Mobil Delvac Legend Antifreeze -35°C Heavy Duty meets the requirements of:

China GB 29743.1-2022

ASTM D6210

ASTM D3306

Mobil Delvac Legend Antifreeze -35°C Heavy Duty is recommended by ExxonMobil for use in applications requiring

CUMMINS CES 14603

MACK 014GS17004

MAN 324

DETROIT DIESEL 7SE298

Mobil Delvac Legend Antifreeze -35°C Heavy Duty is recommended by ExxonMobil for use in applications requiring

CATERPILLAR EC-1

GM EC-1 HD Truck

KenworthR026-170-97

VOLVO VCS

Typical Properties

	Mobil Delvac Legend Antifreeze -35°C Heavy Duty
Color, Visual	Clear Transparent Red
Freezing Point (°C), ASTM D1177	-35 max.
Boiling Point (°C), ASTM D1120	107.5 min.
Density @ 20°C, SH/T 0068	1.071
pH, ASTM D1287	8.4
Chloride Content (ppm), ASTM D1881	25 max.

Recommended shelf life is 5 years, when stored undercover and away from moisture and direct sunlight.

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2024

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved