



## Mobil Delvac Modern™ 5W-30 City Logistics

Mobil Commercial Vehicle Lube , 中国

Full Synthetic Engine Oil

### Product Description

Mobil Delvac Modern™ 5W-30 City Logistics is a low ash synthetic engine oil and formulated to deliver high performance in light duty commercial diesel engines equipped with a Diesel Particulate Filter (DPF) and is suitable for driving conditions of city logistics applications. Mobil Delvac Modern™ 5W-30 City Logistics provides protection for DPFs and diesel engines under the conditions of frequent start-ups, stop and go drivings.

This product is recommended for use in a wide range of light-duty commercial vehicles like pick-up trucks and light duty diesel engine vehicles requiring ACEA C3.

### Features and Benefits

Mobil Delvac Modern™ 5W-30 City Logistics is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance, Key benefits include:

- Helps to maintain the efficiency of the DPF systems in light duty commercial vehicles.
- Helps to reduced sludge build-up, deposits, and long oil and engine life.
- Helps to maintain good fluidity of oil film in face of high temperature and severe working conditions.

### Applications

Mobil Delvac Modern™ 5W-30 City Logistics offers excellent performance at both very low and very high operating temperatures and long engine protection from wear and sludge and deposit build-up. Mobil Delvac Modern™ 5W-30 City Logistics is recommended for demanding driving conditions:

- Light duty commercial vehicles requiring ACEA C3
- Diesel engine with Diesel Particulate Filters (DPF)

Please refer to the owners handbook for OEM application requirements and oil drain intervals for your vehicle or equipment.

### Specifications and Approvals

**This product meets or exceeds the requirements of:**

ACEA C3

### Properties and Specifications

Property	
Grade	SAE 5W-30
Density @ 15.6 C, g/ml, ASTM D4052	0.857
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	12.35

Property	
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	75.2
Viscosity Index, ASTM D2270	163
Total Base Number, mgKOH/g, ASTM D2896	8.5
Flash Point, Cleveland Open Cup, °C, ASTM D92	222
Pour Point, °C, ASTM D97	-42

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2022

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved