



MOBIL DELVAC™ SUPER 1300 C V2 Series

Mobil Commercial Vehicle Lube , 中国

High Performance Diesel Engine Oil

Product Description

Mobil Delvac Super 1300 C 15W-40/20W-50 V2 are high performance diesel engine oils that provide excellent protection and long engine life for construction equipment. The products are widely used in various applications with benefits of clean engines and wear protection.

Features and Benefits

The key benefits of Mobil Delvac Super 1300 C V2 include :

- Clean engines
- Wear protection
- Oil pressure stability

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
TBN reserve	Deposit control
Stay-in-grade shear stability	Reduced oil consumption and wear protection
Excellent detergency/dispersancy	Clean engines and long engine life

Applications

Recommended by ExxonMobil for use in :

- Diesel engines meeting non-road mobile machinery China III (and below) emission standards
- Off-highway industries including: construction, mining, quarrying, agriculture and diesel oil power generators

Specifications and Approvals

This product meets or exceeds the requirements of:	15W40	20W-50
API CH-4	X	X

Properties and Specifications

Property	15W40	20W-50
Grade	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	1.1	1.1
Density @ 15 C, kg/l, ASTM D4052	0.869	0.872

Property	15W40	20W-50
Flash Point, Cleveland Open Cup, °C, ASTM D92	233	245
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	15.2	20.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	116	174
Pour Point, °C, ASTM D97	-33	-30
Total Base Number, mgKOH/g, ASTM D2896	8	9
Viscosity Index, ASTM D2270	137	135

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

ExxonMobil (China) Investment Co. Ltd
 17th Floor, Metro Tower
 30 Tian Yao Qiao Road
 Shanghai 2000030
 China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved