



Mobil Delvac MX V2 Series

Mobil Commercial Vehicle Lube , 中国

Extra High Performance Diesel Engine Oil

Product Description

Mobil Delvac MX 15W-40/20W-50 V2 are extra high performance diesel engine oils that provide excellent protection and long engine life for construction equipment, including diesel engines with EGR (Exhaust Gas Recirculation). Mobil Delvac MX 15W-40/20W-50 V2 are formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in diesel engines with benefits of long ODI, clean engines, high thermal stability and wear protection.

Features and Benefits

The key benefits of Mobil Delvac MX 15W-40/20W-50 V2 include :

- Clean engines
- High thermal stability and wear protection
- Long ODI"

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduced sludge build-up, deposits and viscosity increase
TBN reserves	Deposit control and acid neutralisation
Stay-in-grade shear stability	Wear protection and viscosity control
Advanced detergency/dispersancy	Clean engines and long component life
Improved soot handling	Viscosity control and used oil pumpability

Applications

Recommended by ExxonMobil for use in :

- Diesel powered equipment, including diesel engines with EGR (Exhaust Gas Recirculation), with engine oil requirement of API CI-4
- On-highway diesel powered equipment with China V and below emission standard(1)
- Off-highway industries including: construction, mining, quarrying, agriculture and diesel oil power generators

* Mixed fleet applications

(1) Applicable to vehicles without DPF; for detailed lubes requirement and application, please refer to the service manual

Specifications and Approvals

This product is recommended for use in applications requiring:	MOBIL DELVAC MX 15W-40 V2	MOBIL DELVAC MX 20W-50 V2
API CF	X	

This product meets or exceeds the requirements of:	MOBIL DELVAC MX 15W-40 V2	MOBIL DELVAC MX 20W-50 V2
API CH-4	X	
API CI-4	X	X
API SL	X	
ACEA E7	X	

Properties and Specifications

Property	MOBIL DELVAC MX 15W-40 V2	MOBIL DELVAC MX 20W-50 V2
Grade	SAE 15W-40	SAE 20W-50
Ash, Sulfated, mass%, ASTM D874	1.1	1.1
Density @ 15 C, lb/USg, ASTM D4052	0.869	0.88
Flash Point, Cleveland Open Cup, °C, ASTM D92	225	227
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.6	19.3
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	110	169
Pour Point, °C, ASTM D97	-36	-30
Total Base Number, mgKOH/g, ASTM D2896	9	9
Viscosity Index, ASTM D2270	136	130

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2020

ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved