



Mobil Delvac™ City Logistics 15W-40

Mobil Commercial Vehicle Lube , 中国

High Performance Diesel Engine Oil

Product Description

Mobil Delvac™ City Logistics 15W-40 is a high performance diesel engine oil that provides engine protection of diesel engines operating in frequent start-stop environment for intra-city and inter-city logistics. Mobil Delvac™ City Logistics 15W-40 is recommended by ExxonMobil for use in a wide range of traditional light-duty commercial vehicles.

Features and Benefits

The key benefits of Mobil Delvac™ City Logistics 15W-40 include:

Features	Advantages and Potential Benefits
Thermal and oxidation stability	Controls sludge build-up and deposits
Excellent detergency/dispersancy	Clean engines and long engine life
Stay-in-grade shear stability	Reduced oil consumption and effective wear protection

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On-highway light-duty trucking

Specifications and Approvals

Mobil Delvac™ City Logistics 15W-40 is recommended by ExxonMobil for use in applications requiring:
API CF-4/CD
API SH
ACEA E2
MAN 271

Typical Properties

SAE Grade	15W-40
Viscosity, ASTM D 445	
cSt @ 40°C	111
cSt @ 100°C	14.3
Viscosity Index, ASTM D 2270	130

SAE Grade	15W-40
Sulfated Ash, wt%, ASTM D 874	0.9
Total Base Number, mg KOH/g, ASTM D 2896	8
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	238
Density @ 15°C, kg/L, ASTM D 4052	0.877

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil™ logotype, the Pegasus design, Mobil Delvac™ and Mobil Delvac Super™ are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

05-2020

ExxonMobil (China) Investment Co. Ltd
 17th Floor, Metro Tower
 30 Tian Yao Qiao Road
 Shanghai 2000030
 China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved