



Mobil Super™ 3000 Formula V 0W-40

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

MOBIL SUPER™ 3000 FORMULA V 0W-40 is full synthetic engine oils, designed to provide outstanding levels of protection and performance.

Features and Benefits

- Outstanding wear protection
- Outstanding engine cleanliness
- Outstanding high temperature protection
- Outstanding low temperature protection

Applications

MOBIL SUPER™ 3000 FORMULA V 0W-40 is formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We parti recommend MOBIL SUPER 3000 FORMULA V 0W-40 if you regularly experience demanding conditions where it can help combat the damage caused by frequer engine stress.

Specifications and Approvals

This product has the following approvals:
VW502 00
VW505 00

This product meets or exceeds the requirements of:
APISN
ACEA A3/B3
ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 0W-40
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	74

Property	
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.6
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	30600
Density @ 60 F, kg/m3, ASTM D4052	0.836
Total Base Number, mgKOH/g, ASTM D2896	10.1
Ash, Sulfated, mass%, ASTM D874	1.1
Pour Point, °C, ASTM D97	-48
Flash Point, °C, ASTM D92	230

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2023
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved