



## MOBIL ATF 8LV

Mobil Passenger Vehicle Lube , 中国

Automatic Transmission Fluid

### Product Description

Mobil ATF 8LV is a premium full synthetic lubricant formulated for use in a wide variety of North American, European, and Asian vehicles equipped with 6-8 speed automatic transmissions.

### Features and Benefits

- Exceptional oxidation stability and enhanced elastomer compatibility — maintains long-lasting fluid quality and helps prolong transmission life
- Corrosion prevention – helps provide protection against rusting and corrosion, plus special protection for soldered fittings
- Low temperature fluidity for smooth start-up, plus exceptional viscosity stability at high operating temperatures
- Excellent lubricating characteristics for quiet operation, smooth shifting, and uncompromised anti-wear protection
- better fuel economy potential with low viscosity solution\*

### Applications

Mobil ATF 8LV is a full synthetic automatic transmission fluid designed to meet the needs of the broadest range of transmission designs. Mobil ATF 8LV recommended for use in CVT or DCT transmissions.

Good maintenance practice dictates that automatic transmissions be checked for proper fluid levels at regular intervals, and that the fluid be drained and replaced at intervals recommended by the manufacturer. Some manufacturers recommend more frequent changes of transmission fluid under severe driving conditions such as those that occur in heavy traffic, in hot weather, or when pulling a trailer.

Based on a combination of field-testing and laboratory testing, Mobil ATF 8LV is suitable for use in applications requiring Dexron VI, Mercon LV, JASO 1A LV, etc.

Mobil ATF 8LV is suitable for use in a broad range of transmissions. The list below is just a sample of applications where combined test results support the use of ATF 8LV. It is important to note that the respective vehicle manufacturers have neither evaluated nor approved Multi-vehicle ATF in these applications except as noted in the Specifications and Approvals section.

Mobil ATF 8LV is suitable for use in many passenger vehicles including:

- Audi
- BMW / MINI
- Ford
- GM
- Honda
- Hyundai
- Jaguar
- Kia
- Land Rover
- Nissan
- Toyota
- VW

Specifications and Approvals

|  |  |
|--|--|
| This product is recommended for use in applications requiring: |  |
| BMW 83 22 0 142 516  |  |
| BMW 83 22 0 397 114  |  |
| BMW 83 22 2 152 426  |  |
| BMW 83 22 2 289 720 (BMW ATF 3+)                               |  |
| BMW 83 22 2 305 397 (BMW ATF 3)                                |  |
| FORD Mercon LV   |  |
| GM Dexron VI   |  |
| Honda ATF DW-1   |  |
| Honda Type 2.0   |  |
| Honda Type 3.0   |  |
| Hyundai SP-IV  |  |
| Jaguar Fluid 8432  |  |
| Jaguar Fluid JDE 26444   |  |
| NISSAN Matic S   |  |
| NISSAN Matic W   |  |
| TOYOTA WS  |  |
| VW TL 52162  |  |
| VW TL 52540-B  |  |
| ZF TE-ML 11 (6 speeds)   |  |
| ZF TE-ML 11 (8 & 9 speeds)                                     |  |

|  |  |
|--|--|
| This product meets or exceeds the requirements of: |  |
| JASO 1-A-LV-15                                     |  |

Properties and Specifications

| Property                                 |       |
|--|-------|
| Kinematic Viscosity 40 C, cSt, ASTM D445 | 30    |
| Pour Point, °C, ASTM D5950               | -45   |
| Density @ 15 C, g/cm3, ASTM D4052        | 0.849 |

| Property  |       |
|---|-------|
| Kinematic Viscosity 100 C, cSt, ASTM D445       | 6.1   |
| Brookfield Viscosity @ -40 C, mPa.s, ASTM D2983 | 11200 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92   | 204   |
| Color, Visual                                   | Amber |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022  
ExxonMobil (China) Investment Co. Ltd  
17th Floor, Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 2000030  
China

+86 21 24076000  
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

ATTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved