



Mobil Super™ Synthetic Technology 5W-30

Mobil Passenger Vehicle Lube , 中国

Synthetic Technology Engine Oil

Product Description

Mobil Super™ Synthetic Technology 5W-30 is a synthetic technology engine oils designed to provide a high level of performance and protection under most operating conditions.

Features and Benefits

Mobil Super™ Synthetic Technology 5W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection and extends engine life.

- Designed to provide very good wear protection
- Helps to maintain engine cleanliness

Applications

Mobil Super™ Synthetic Technology 5W-30 is suitable for use in gasoline powered vehicles.

Specifications and Approvals

This product is recommended for use in applications requiring:
Ford WSS-M2C929-A
GM 6094M
API CF
This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SN PLUS RESOURCE CONSERVING
API SN Resource Conserving
API SP
API SP Resource Conserving
ILSAC GF-6A
Ford WSS-M2C946-A
Ford WSS-M2C946-B1

This product meets or exceeds the requirements of:
FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Flash Point, Cleveland Open Cup, °C, ASTM D92	228
Pour Point, °C, ASTM D97	-39
Viscosity Index, ASTM D2270	151
Total Base Number, mgKOH/g, ASTM D2896	7.5
Density @ 15.6 C, g/ml, ASTM D4052	0.859
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.3
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	63
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	16400
Ash, Sulfated, mass%, ASTM D874	0.8

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2023
ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000
<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved