# Mobil

## APZHMOBIL SYNTHETIC 5W30 MT80

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

### Product Description

Mobil Synthetic 5W-30 (MT80) is a full synthetic engine oil which meets with API SP grade, designed to keep you worry free from various road condition.

#### Features and Benefits

meet with API SP grade allows easy and smooth starting during cold starts with good fluidity in low temperature it protects the engine in high temperature and keeps engine clean ability of controlling ashes, meet with China 6.

#### Applications

Mobil Synthetic 5W-30 (MT80) is recommended for gasoline vehicles with 5W-30 visosity grade recommended.

#### Specifications and Approvals

This product meets or exceeds the requirements of:	
APISP	
ILSAC GF-6A	

#### Properties and Specifications

Property	
Grade	SAE 5W-30
Ash, Sulfated, mass%, ASTM D874	0.8
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	13800
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.1
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	64
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.7
Density @ 15.6 C, g/ml, ASTM D4052	0.857
Total Base Number, mgKOH/g, ASTM D2896	8.5
Viscosity Index, ASTM D2270	158
Flash Point, Cleveland Open Cup, °C, ASTM D92	228

Property	
Pour Point, °C, ASTM D97	-36

#### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ http://www.msds.exxonmobil.com/psims/psims.as All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2022 ExxonMobil (China) Investment Co. Ltd 17th Floor, Metro Tower 30 Tian Yao Qiao Road Shanghai 2000030 China

#### +86 21 24076000 http://www.exxonmobil.com

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All primary not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intenoverride or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

Exon Mobil exon Mobil Cosporation. All Rights Reserved