



Mobil 1™ 0W-20

Mobil Passenger Vehicle Lube , 中国

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ is the world's leading synthetic motor oil brand delivering our ultimate performance and protection.

Mobil 1™ 0W-20 is an advanced full synthetic engine oil designed delivering great engine performance beyond conventional engine oils. Mobil 1 0W-20 is engineered for gasoline engine technology delivering excellent all-round performance. It provides exceptional cleaning power, wear protection and overall performance even during longer oil change intervals. Mobil 1 0W-20 keeps your engine running like new in all driving conditions.

Features and Benefits

Mobil 1 0W-20 is engineered with a proprietary blend of high performance synthetic basestocks fortified with a precisely balanced component additive system. The low viscosity, advanced full synthetic formulation helps to increase engine efficiency and improve fuel economy. Mobil 1 0W-20 provide excellent high-temperature protection while offering the best fuel economy in the Mobil 1 line. Key features and potential benefits include:

- Successfully challenged 18,000 KMs Oil Drain Interval*
- Keeps your engine running like new
- Our ultimate Engine Performance and Wear Protection
- Enhanced Frictional Properties, excellent Fuel Economy
- Excellent Low Temperature properties for Rapid Protection at Start-Up
- Keeps your engine clean
- Protects engines working under high temperatures

* Proven by actual road test in China (18,000 KMs oil drain interval and 167,000 KMs distance traveled on the road)

Applications

Mobil 1 0W-20 is recommended for many types of modern vehicles where it will help provide the performance required even under very demanding driving conditions.

- Latest gasoline engine technologies including high performance, turbo-charged, direct injection and hybrids found in passenger cars, SUVs, light vans and trucks
- Most operating conditions, from mild to extreme

Specifications and Approvals

This product has the following approvals:

GM dexos1:GEN2 Licensed

This product is recommended for use in applications requiring:

API CF

GM 6094M

This product is recommended for use in applications requiring:

Fiat Chrysler Automotive MS-6395

This product meets or exceeds the requirements of:

API SM

API SL

API SJ

Ford WSS-M2C947-A

API SN PLUS

Ford WSS-M2C947-B1

API SN PLUS RESOURCE CONSERVING

API SN

Properties and Specifications

Property	
Grade	SAE 0W-20
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	8.8
Flash Point, Cleveland Open Cup, °C, ASTM D92	224
Density @ 15.6 C, g/cm ³ , ASTM D4052	0.839
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	45

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

03-2021

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is

intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved