



## Mobil 1™ Silver 0W-40

Mobil Passenger Vehicle Lube , 中国

Advanced Full Synthetic Engine Oil

### Product Description

Mobil 1™ Silver 0W-40 is an advanced full synthetic motor oil engineered for the latest gasoline and diesel engine technology (without GPFs and DPFs) delivering excellent all-around performance. Mobil 1™ Silver 0W-40 keeps your engine running like new.

### Features and Benefits

1. Meets or exceeds the latest OEM and industry approvals
2. Provides excellent overall performance
3. Keeps Your Engine Running Like New\*

\* Based on MADS testing.

### Applications

Mobil 1™ Silver 0W-40 is recommended for many types of modern vehicles where it will help provide unsurpassed performance even under very demanding driving conditions.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

This product has the following approvals:
MB-Approval 229.5
VW 502 00
VW 505 00

This product meets or exceeds the requirements of:
API SP
ACEA A3/B4

### Properties and Specifications

Property	
Grade	SAE 0W-40
Pour Point, °C, ASTM D97	-45

Property	
Viscosity Index, ASTM D2270	180
Density @ 15.6 C, g/ml, ASTM D4052	0.839
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.5
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	77
Flash Point, Cleveland Open Cup, °C, ASTM D92	233
Ash, Sulfated, mass%, ASTM D874	1.2
Total Base Number, mgKOH/g, ASTM D2896	12.5
Mini-Rotary Viscometer, Apparent Viscosity, -40 C, mPa.s, ASTM D4684	28200

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

ExxonMobil (China) Investment Co. Ltd  
17th Floor, Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 2000030  
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved