



Mobil Special™ Full Synthetic 5W-30

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

Mobil Special™ Full Synthetic 5W-30 is a entry level full synthetic engine oils, designed to provide trustworthy caring for engines for daily driving.

Features and Benefits

Updated full synthetic formulation to provide more stable oil film for better enging protection

Provide anti-wear protection, sludge cleanness protection to bring trustworthy daily engine protection

Applications

Mobil Special™ Full Synthetic 5W-30 is suitable for engines which needs 5W-30 viscosity engine oil and require reliable protection in daily driving in normal road condition.

Specifications and Approvals

This product meets or exceeds the requirements of:

API SM

API SN

Properties and Specifications

Property	
Grade	SAE 5W-30
Viscosity Index, ASTM D2270	151
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.1
Density @ 15 C, kg/l, ASTM D4052	0.86
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	62
Flash Point, Cleveland Open Cup, °C, ASTM D92	223
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.1
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	15500
Total Base Number, mgKOH/g, ASTM D2896	6.8

Property	
Ash, Sulfated, mass%, ASTM D874	0.8
Pour Point, °C, ASTM D97	-36

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2024

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved