



## Mobil Super™ 1000 X2 15W-40

Mobil Passenger Vehicle Lube , 中国

Premium Multigrade Passenger Vehicle Engine Oil

### Product Description

Mobil Super™ 1000 X2 15W-40 is a premium conventional engine oil, designed to provide a high level of protection and performance.

### Features and Benefits

Mobil Super 1000 X2 15W-40 is industry proven so you can be assured that your vehicle is well protected from city driving.

Mobil Super 1000 X2 15W-40 provides:

- Good wear protection
- Good engine cleanliness
- Good high temperature protection

### Applications

Mobil Super 1000 X2 15W-40 is formulated to be suitable for use in nearly all vehicles. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal Operating Conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

| This product has the following approvals: |
|---|
| MB-Approval 229.1                         |
| VW 501 01                                 |
| VW 505 00                                 |

| This product is recommended by ExxonMobil for use in applications requiring: |
|--|
| API CF   |

| This product meets or exceeds the requirements of: |
|--|
|--|

**This product meets or exceeds the requirements of:**

API SJ

API SL

API SM

API SN

API SN PLUS

ACEA A3/B3

**Properties and Specifications**

| Property  |            |
|---|------------|
| Grade   | SAE 15W-40 |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445            | 14.5       |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445             | 104        |
| Viscosity Index, ASTM D2270   | 143        |
| Density @ 15.6 C, g/ml, ASTM D4052                                    | 0.873      |
| Pour Point, °C, ASTM D97  | -39        |
| Flash Point, Cleveland Open Cup, °C, ASTM D92                         | 239        |
| Ash, Sulfated, mass%, ASTM D874                                       | 0.9        |
| Total Base Number, mgKOH/g, ASTM D2896                                | 10         |
| Mini-Rotary Viscometer, Apparent Viscosity, -25 C, mPa.s, ASTM D4684  | 14600      |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 3.9        |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

10-2022

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect

product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved