



## Mobil Super™ 2000 Synthetic 5W-40

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

### Product Description

Mobil Super™ 2000 Synthetic 5W-40 is full synthetic engine oils, designed to provide fast protection for engines against tough conditions in city driving.

### Features and Benefits

Mobil Super™ 2000 Synthetic 5W-40 provides:

- Outstanding anti-wear protection for vehicles of all ages against tough conditions in city driving.
- Outstanding protection against harmful deposits to maintain engine cleanliness.
- Outstanding protection against LSPI (low speed pre-ignition) events in TGDI engines to help prolong engine life.
- Low temperature fluidity for smooth start-up, plus exceptional viscosity stability at high operating temperatures.

### Applications

Mobil Super™ 2000 Synthetic 5W-40 is formulated to give you confidence of engine protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Passenger cars, SUV's, and high performance vehicles
- Engines with Turbo-Chargers
- Highway cruising
- Normal to occasionally severe operating conditions
- Stop and Go City Driving

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

<b>This product is recommended for use in applications requiring:</b>
API CF

<b>This product meets or exceeds the requirements of:</b>
API SL
API SM
API SN
API SN PLUS

**This product meets or exceeds the requirements of:**

API SP

### Properties and Specifications

Property	
Grade	SAE 5W-40
Density @ 15.6 C, g/ml, ASTM D4052	0.858
Pour Point, °C, ASTM D97	-42
Ash, Sulfated, mass%, ASTM D874	0.8
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	40100
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	86
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.1
Total Base Number, mgKOH/g, ASTM D2896	8.5
Viscosity Index, ASTM D2270	170
Flash Point, Cleveland Open Cup, °C, ASTM D92	215

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2023

ExxonMobil (China) Investment Co. Ltd  
17th Floor, Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 2000030  
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved