



Mobil Super™ 2000 x3 5W-40

Mobil Passenger Vehicle Lube , 中国

Full Synthetic Engine Oil

Product Description

MOBIL SUPER 2000 X3 5W-40 is a full synthetic engine oil which meets with API SN PLUS grade, designed to keep you worry free from various road condition and provide protection to engine.

Features and Benefits

- It provides stable oil film no matter in high or low temperature.
- It provides engine strong wear protection
- Allows easy starting and rapid oil circulation during cold starts to protect critical engine parts
- Meets or exceeds the latest industry specifications

Applications

MOBIL SUPER 2000 X3 5W-40 is recommended for both gasoline and light duty diesel vehicles with 5W-40 viscosity grade.

Specifications and Approvals

This product has the following approvals:

MB-Approval 229.3

VW 502 00

VW 505 00

This product meets or exceeds the requirements of:

API SN PLUS

ACEA A3/B3

ACEA A3/B4

Properties and Specifications

Property	
Grade	SAE 5W-40
Ash, Sulfated, mass%, ASTM D874	1.1

Property	
Pour Point, °C, ASTM D97	-42
Viscosity Index, ASTM D2270	165
Total Base Number, mgKOH/g, ASTM D2896	10
Mini-Rotary Viscometer, Apparent Viscosity, -35 C, mPa.s, ASTM D4684	29300
Density @ 15 C, g/ml, ASTM D1298	0.859
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.5
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	81

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

08-2022

ExxonMobil (China) Investment Co. Ltd

17th Floor, Metro Tower

30 Tian Yao Qiao Road

Shanghai 2000030

China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved