



Mobil™ Super 4T 10W-40

Mobil Passenger Vehicle Lube , 中国

Four-Stroke Motorcycle Engine Oil

Product Description

Mobil™ Super 4T 10W-40 is a high performance engine oil for modern motorcycle engines, though developed for latest engine technology, Mobil™ Super 4T 10W-40 provides good protection for conventional technology engine too.

Features and Benefits

Mobil™ Super 4T 10W-40 combine high quality base oils and an advanced additive system to help extend the life of engine system:

Key features and benefits include:

Features	Advantages and Potential Benefits
Outstanding wear protection	Helps prevent engine system from wearing
Thermal and oxidation stability	Helps keep engines clean for smoother operation
Excellent corrosion protection	Protects critical engine components from corrosion
High friction performance	Helps prevent clutch slippage and maintain optimal performance
Enhanced high and low temperature performance	Smooth start at low temperature and stable control when high temperature

Applications

Mobil™ Super 4T 10W-40 is a high-performance motorcycle oil that provides good protection for engines and gears of all types of four-stroke motorcycles (except scooters) and allows the clutch to operate smoothly.

- Best for the modern four-stroke motorcycle engines JASO MA or JASO MA2 recommended by OEMs.
- Good protection to motorcycle engines before introduction of JASO MA or JASO MA2.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SN
JASO MA2

Properties and Specifications

Property	
Grade	SAE 10W-40

Property	
Mini-Rotary Viscometer, Apparent Viscosity, -30 C, mPa.s, ASTM D4684	12300
Pour Point, °C, ASTM D97	-36
Total Base Number, mgKOH/g, ASTM D2896	6.7
Ash, Sulfated, mass%, ASTM D874	0.7
Flash Point, Cleveland Open Cup, °C, ASTM D92	236
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	92
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.6
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	13.2
Density @ 15.6 C, g/ml, ASTM D4052	0.864
Viscosity Index, ASTM D2270	144

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2024

ExxonMobil (China) Investment Co. Ltd
17th Floor, Metro Tower
30 Tian Yao Qiao Road
Shanghai 2000030
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved