



Mobil Delvac™ 1300 Super 15W-40

Mobil Commercial Vehicle Lube , Colombia

Mobil Passenger Vehicle Lube

Product Description

MOBIL Delvac 1300 Super 15W-40 is a mineral technology, diesel engine oils that help extend engine life, allowing you to run your business with confidence. This product meets or exceed original equipment manufacturer (OEM) requirements and deliver high performance in both on and off-highway applications.

Fully backward compatible, MOBIL Delvac 1300 Super 15W-40 delivers exceptional performance in both newer and older heavy duty engine designs. Accordingly, this oil meets or exceed the requirements of API CK-4, CJ-4, CI-4 PLUS, CI-4 and CH-4 service categories, as well as key OEM requirements. MOBIL Delvac 1300 Super 15W-40 may also be used in gasoline engines requiring the API SN specification.

Developed in close collaboration with major OEMs, MOBIL Delvac 1300 Super 15W-40 is recommended for use in a wide range of heavy duty applications and operating environments.

Features and Benefits

MOBIL Delvac 1300 Super 15W-40 is formulated to deliver extended performance for up to 50% beyond OEM-recommended oil drain intervals¹. This proprietary mineral technology formulation delivers up to an average of 50 % more wear protection than required in API CK-4 engine tests , outstanding oxidation stability, and outstanding TBN retention.

MOBIL Delvac 1300 Super 15W-40 also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

¹ Based on US engine manufacturers' (OEM) average oil drain intervals (ODI) API CK-4 / API FA-4 recommendation. Results vary based on vehicle/engine condition, driving and environmental conditions. Consult OEM or ExxonMobil before implementing extended ODIs, especially if the equipment/vehicle is under warranty.

Features	Advantages and Potential Benefits
Outstanding oxidation stability	Extended ODI potential up to 1.5X the average OEM ODI recommendation ¹ .
Resistance to corrosive and abrasive wear	Provides up to an average of 50 % more wear protection than required in API CK-4 engine tests.
Meets demanding specifications of key OEMs and latest API gasoline service category	One engine oil for mixed fleet operations
Excellent soot and viscosity control	Greater engine efficiency, long engine life and long oil life.
Excellent oil consumption control	Lower oil costs due to less make-up oil during operation
Outstanding TBN reserves	Corrosion protection and extended drain intervals for both new and old engines
Low temperature fluidity and pumpability	Formulated for smooth starting in cold weather
Component compatibility	Long gasket and seal life

Features	Advantages and Potential Benefits
Low ash formulation meeting API CK-4 and CJ-4 requirements	Long emissions aftertreatment life (DPF, DOC and SCR)

Applications

MOBIL Delvac 1300 Super 15W-40 is formulated to deliver extended performance for up to 50% beyond OEM-recommended oil drain intervals¹. This proprietary mineral technology formulation delivers up to an average of 50 % more wear protection than required in API CK-4 engine tests, outstanding oxidation stability, and outstanding TBN retention.

MOBIL Delvac 1300 Super 15W-40 also provides outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear, and high temperature deposits.

Specifications and Approvals

This product has the following approvals:
Detroit Detroit Fluids Specification 93K222
Detroit Fluids Specification 93K218
DEUTZ DQC II-10 LA
Mack EO-N Premium Plus 03
Mack EO-O Premium Plus
MACK EOS-4.5
MB-Approval 228.31
RENAULT TRUCKS RLD-3
VOLVO VDS-2
VOLVO VDS-3
VOLVO VDS-4
VOLVO VDS-4.5

This product is recommended for use in applications requiring:
API CF
API CF-2
API CF-4
API CG-4
MAN M 3275-1
MAN M 3575

This product meets or exceeds the requirements of:

API CH-4

API CI-4

API CI-4 PLUS

API CJ-4

API CK-4

API SL

API SM

API SN

API SP

JASO DH-2

ACEA E7

ACEA E9

Caterpillar ECF-3

Cummins CES 20081

Cummins CES 20086

Properties and Specifications

Property	
Grade	SAE 15W-40
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	109.8
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.8
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10 ⁶ sec ⁻¹ , mPa.s, ASTM D4683	4.1
Flash Point, Cleveland Open Cup, °C, ASTM D92	226
Ash, Sulfated, mass%, ASTM D874	0.9
Density @ 15 C, g/ml, ASTM D1298	0.87
Pour Point, °C, ASTM D97	-42
Total Base Number, mgKOH/g, ASTM D4739	9.7

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2021

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO

© Copyright 2003-2021 Exxon Mobil Corporation. All Rights Reserved