



MOBIL DELVAC MODERN™ 15W-40 NV TRACK

Mobil Commercial Vehicle Lube , Colombia

High-performance diesel engine oil

Product Description

Mobil Delvac Modern™ 15W-40 NV Track is a high performance diesel engine oil that provides excellent lubrication for today's diesel engines, enabling long engine life. It provides exceptional performance in modern and demanding low-emission diesel engines. Mobil Delvac Modern™ 15W-40 NV Track combines a blend of high-performance base oils with a progressive additive system to provide superior control of oil thickening due to soot buildup and high temperatures, as well as outstanding resistance to oxidation, corrosion and deposits caused by high temperatures.

Features and Benefits

High-power, low-emission diesel engines significantly increase the demands on engine lubricants, so Mobil Delvac Modern™ 15W-40 NV Track has the following features and benefits:

Features	Advantages and Potential Benefits
High thermal and oxidation stability	Reduction of sludge and deposit accumulation and increased viscosity
TBN reserves	Deposit control and acid neutralization
Shear stability	Wear protection and viscosity control
Advanced Detergency/Dispersance	Cleaner engines and longer component life
Better soot handling	Better control of the viscosity and pumping capacity of used oil
Excellent low-temperature properties	Wear protection during start-up
Component compatibility	Longer shelf life of gaskets and seals

Applications

Recommended by ExxonMobil for use in:

- Applications requiring Cummins CES 20076/CES20077/CES20078 service level.
- Light and heavy duty vehicles.
- Off-road industries, including: construction, mining, quarrying and agriculture.
- Mixed fleet applications.

Specifications and Approvals

This product meets or exceeds the requirements of:
API CI-4

Properties and Specifications

Property	
-----------------	--

Property	
Grade	SAE 15W-40
Pour Point, °C, ASTM D97	-33
Total Base Number, mgKOH/g, ASTM D2896	11.5
Density @ 15.6 C, kg/l, ASTM D4052	0.88
Viscosity Index, ASTM D2270	137
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.38
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	105.6
Flash Point, Cleveland Open Cup, °C, ASTM D92	225
Ash, Sulfated, mass%, ASTM D874	1.3

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2022

Organización Terpel S.A.



Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil

Exxon Mobil  

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved