



Mobil Delvac Legend™ 1340

Mobil Commercial Vehicle Lube , Colombia

Monograde diesel engine oil

Product Description

Mobil Delvac Legend™ 1320, 1330, 1340, and 1350 are high performance monograde diesel engine oils formulated from advanced technology base oils and a balanced additive system. They are specifically engineered for performance in intercooled, turbo-charged engines operating under severe on and off-highway conditions. Mobil Delvac Legend 1300 are used in a wide range of applications where a monograde lubricant is recommended.

Features and Benefits

The features and benefits of Mobil Delvac Legend 1300 Series include

Features	Advantages and Potential Benefits
Excellent protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion.	Prolonged engine life. Less wear. Excellent protection against ring sticking.
Extended TBN reserve	Long-term deposit/wear control. Controls formation of acids when using higher sulfur fuels.

Applications

Naturally aspirated and turbo-charged diesel powered equipment

On highway light and heavy duty trucking

Off highway industries including: construction, mining, quarrying, and agriculture

Hydraulic system and wet breaks in mobile equipment where a SAE 20 diesel engine oil is required (Mobil Delvac Legend 1320)

Suitable for use on applications requiring MB 227 specification

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF
API SF

Properties and Specifications

Property	

Property	
Grade	SAE 40
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	14.3
Pour Point, °C, ASTM D97	-21
Flash Point, Cleveland Open Cup, °C, ASTM D92	246
Total Base Number, mgKOH/g, ASTM D2896	10
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	142
Density @ 15 C, g/cm ³ , ASTM D4052	0.82

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

09-2023

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved