



Mobil Gargoyle Arctic SHC 226

Mobil Industrial , Colombia

Refrigeration Oil

Product Description

The Mobil Gargoyle Arctic SHC 226 is a full synthetic, superior performance lubricant, specifically designed for use in refrigeration compressors and heat pumps. Formulated from wax-free, synthesised hydrocarbon polyalphaolefin (PAO) fluids, which have outstanding resistance to thermal/oxidative degradation. With naturally high shear stable viscosity indexes and low temperature fluidity, is able to perform in severe service conditions that are beyond the capabilities of conventional mineral oils. Mobil Gargoyle Arctic SHC 226 solubility and miscibility with commonly used refrigerants is low, resulting in higher film thickness in the presence of refrigerants under pressure. This can help to reduce shaft seal leakage. Mobil Gargoyle Arctic SHC 226 stability and low volatility characteristics reduce "light end stripping" which can occur with conventional mineral oils.

Features and Benefits

The Mobil Gargoyle Arctic SHC brand of lubricants are recognized and appreciated for their innovation and outstanding performance. Our work with equipment builders has helped confirm the results from our own laboratory tests showing the exceptional performance of the Mobil Gargoyle Arctic SHC 200 Series lubricants. Not among the benefits shown in work with OEMs is the superb low temperature capability providing excellent fluidity at low temperatures, as well as the resistance to viscosity loss due to refrigerant absorption under pressure, along with providing excellent bearing film thickness and shaft sealing properties.

Features	Advantages and Potential Benefits
High oil film thickness in the presence of refrigerant	Improved compressor protection for extended compressor life as well as better shaft sealing, reduced bearing failure and less unscheduled downtime
Excellent thermal/oxidative and chemical stability	Long oil life and reduced frequency of drain intervals and routine maintenance
Low volatility	Reduced lacquer and deposit formation
High Viscosity Index and wax-free	Viscosity remains consistent with reduced oil consumption
Low traction coefficient	Excellent low temperature fluidity, no waxy deposits and improved evaporator efficiency
Seal compatibility	Potential for improved system efficiency and reduced power consumption
	Long seal life, reduced shaft seal leakage

Applications

Mobil Gargoyle Arctic SHC 226 is recommended for the lubrication of refrigeration compressors operating at very high temperatures, and for systems with very low evaporator temperatures. It is suitable for compressor systems using refrigerants such as ammonia and carbon dioxide. Mobil Gargoyle Arctic SHC 226 is compatible with most common refrigerants, except sulphur dioxide, and have been particularly successful in systems using ammonia as the refrigerant. Mobil Gargoyle Arctic SHC 226 is fully miscible with most conventional mineral refrigeration oils. Any mixture with mineral oils may detract from the outstanding performance properties of the synthetic product.

Specifications and Approvals

This product is registered to the requirements of:
NSF H1
This product meets or exceeds the requirements of:
FDA 21 CFR 178.3570

Properties and Specifications

Property	
Grade	ISO 68
Flash Point, Cleveland Open Cup, °C, ASTM D92	250
Foam, Sequence I, Stability, ml, ASTM D892	0
Foam, Sequence I, Tendency, ml, ASTM D892	10
Pour Point, °C, ASTM D97	-45
Viscosity Index, ASTM D2270	145
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.4
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	68
Specific Gravity, 15 C/15 C, ASTM D1298	0.83

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

02-2023

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product perfor are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All pr may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is inten override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved