



MOBIL SUPER™ 4T MX SERIES

Mobil Passenger Vehicle Lube , Colombia

Product Description

Mobil Super™4T MX are high performance semi-synthetic four-stroke motorcycle engine oils primarily intended for general use in many types of four-stroke moto and engines. It's unique formulation provides excellent flow characteristics to reduce engine wear during start-up and outstanding protection of the transmission a clutch during operation. Its lower viscosity grades helps the engine to work at a higher level of efficiency, compared to SAE 20W-50.

Features and Benefits

Mobil Super 4T MX provides good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

- Provides anti-wear protection to help promote long engine and transmission life
- Helps keep your engine cleaner
- Formulated with premium base stocks for increased oxidation stability and less volatility.
- Potential fuel economy compared with oil 20W-50 viscosity which can help reduce emissions.
- Excellent frictional properties for proper performance of the clutch.

Applications

Mobil Super 4T MX oils are a product of an advanced blend of mineral and synthetic bases recommended for 4-stroke motorcycle in which the manufacturer specif use of SAE 10W-30,10W- 40 and 15W-50. Its formulation provides the adequate level of protection for the engine transmission and clutch, particularly in air- engines, which tend to operate at higher temperatures. It is also especially recommended for 4-stroke engines equipped with catalytic converters to reduce emissio recommended by ExxonMobil for applications requiring API SL oils. Meets or exceeds the latest JASO MA/MA2 performance standard.

Specifications and Approvals

This product meets or exceeds the requirements of:	10W-30	10W-40	15W-50
API SL	X	X	X
JASO MA 2016	X	X	X
JASO MA2 2016	X	X	X

Properties and Specifications

Property	10W-30	10W-40	15W-50
Grade	SAE 10W-30	SAE 10W-40	SAE 15W-50
Ash, Sulfated, mass%, ASTM D874	0.8	0.74	0.74
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	212	205	208
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.5	13.7	17.8
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	70.5	94.3	133.7
Pour Point, °C, ASTM D97	-33	-42	-39

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

06-2023

Organización Terpel S.A.


Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All properties may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved