

**Mobil Outboard™ Plus 10W-40 FC-W**

Mobil Passenger Vehicle Lube , Colombia

Superior Performance Four-Stroke Outboard Engine Oil

**Product Description**

Mobil Outboard™ Plus 10W-40 FC-W is a high performance, four-stroke engine oil that is designed for many high performance, water-cooled four-stroke engine in outboard marine applications. Mobil Outboard Plus offers clean engine and environmental performance.

**Features and Benefits**

Mobil Outboard™ Plus 10W-40 FC-W is formulated from high purified conventional mineral oils providing outstanding protection against corrosion and wear. Spark fouling and pre-ignition are also minimized promoting flawless operation. The product is ideal for use in both modern and older four-stroke engine models.

**Applications**

Mobil Outboard™ Plus 10W-40 FC-W is recommended by ExxonMobil for use in modern high-performance, water-cooled, four-stroke engines. ExxonMobil recommends Mobil Outboard Plus for use in four-stroke engines where NMMA FC-W oils are recommended.

**Specifications and Approvals****This product meets or exceeds the requirements of:**

NMMA FC-W

**Properties and Specifications**

Property	
Grade	SAE 10W-40
Viscosity Index, ASTM D2270	146
Density @ 15.6 C, g/ml, ASTM D4052	0.86
Flash Point, Cleveland Open Cup, °C, ASTM D92	240
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	94.4
Pour Point, °C, ASTM D97	-39
Total Base Number, mgKOH/g, ASTM D4739	7.2
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	13.6

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>  
All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

11-2022

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved