



## Mobil Super™ 4T MX 15W-50

Mobil Passenger Vehicle Lube , Colombia

Semi-Synthetic High Performance Four-Stroke Motorcycle Engine Oil

### Product Description

Mobil Super™ 4T MX 15W-50 is a high performance semi-synthetic four-stroke motorcycle engine oil primarily intended for general use in many types of four-motorcycles and engines. It's unique formulation provides excellent flow characteristics to reduce engine wear during start-up and outstanding protection transmission and the clutch during operation.

### Features and Benefits

Mobil Super 4T MX 15W-50 provides good engine cleanliness, good wear protection and corrosion protection. Key features and benefits include:

- Provides anti-wear protection to help promote long engine and transmission life
- Helps keep your engine cleaner
- Formulated with premium base stocks for increased oxidation stability and less volatility.
- Excellent frictional properties for proper performance of the clutch.

### Applications

Mobil Super 4T MX 15W-50 oil is a product of an advanced blend of mineral and synthetic bases recommended for 4-stroke motorcycle in which the manufacture specifies the use of SAE 15W-50. Its formulation provides the adequate level of protection for the engine transmission and clutch, particularly in air-cooled engines which tend to operate at higher temperatures.

Meets or exceeds the latest JASO MA performance standard.

### Specifications and Approvals

**This product meets or exceeds the requirements of:**

API SL

JASO MA

JASO MA2

### Properties and Specifications

Property	
Grade	SAE 15W-50
Viscosity Index, ASTM D2270	147
Ash, Sulfated, mass%, ASTM D874	0.76
Pour Point, °C, ASTM D97	-30
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	136.3
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	18.1

Property	
Flash Point, Pensky-Martens Closed Cup, °C, ASTM D93	206
Density @ 15.6 C, g/ml, ASTM D4052	0.87

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2021

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entity.

**ExxonMobil**



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved