



## Mobil Super™ 3000 X1 5W-40

Mobil Passenger Vehicle Lube , Colombia

Premium Full Synthetic Passenger Vehicle Motor Oil

### Product Description

Mobil Super™ 3000 X1 5W-40 is a full synthetic motor oil that provides long engine life for many types & ages of vehicles with enhanced protection over a wide temperature range.

### Features and Benefits

Mobil Super 3000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super™ 3000 X1 5W-40 provides:

- Enhanced high temperature protection
- Enhanced cold start-up performance
- Enhanced engine cleanliness and sludge prevention
- Enhanced wear protection

Features
Enhanced high temperature protection
Enhanced cold start-up performance
Enhanced engine cleanliness and sludge prevention
Enhanced wear protection

### Applications

Mobil Super™ 3000 products are formulated to give you confidence of protection beyond that of conventional or semi-synthetic oils. We particularly recommend Mobil Super™ 3000 if you regularly experience demanding conditions where it can help combat the damage caused by frequent high engine stress:

- Nearly all engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions
- High Performance Engines

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

**This product has the following approvals:**

AVTOVAZ (LADA cars)

MB-Approval 229.3

Peugeot/Citroën Automobiles B71 2296

Porsche A40

RENAULT RN0700

RENAULT RN0710

VW 502 00

VW 505 00

**This product is recommended for use in applications requiring:**

API CF

GM-LL-B-025

**This product meets or exceeds the requirements of:**

AAE (STO 003) Group B6

API SJ

API SL

API SM

API SN

JASO MA

JASO MA2

ACEA A3/B3

ACEA A3/B4

Fiat 9.55535-M2

**Properties and Specifications**

Property	
Grade	SAE 5W-40
Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445	14.2

Property	
Pour Point, °C, ASTM D97	-42
Phosphorus, mass%, ASTM D4951	0.096
Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445	85
Flash Point, Cleveland Open Cup, °C, ASTM D92	222
Ash, Sulfated, mass%, ASTM D874	1.09
Density @ 15.6 C, g/ml, ASTM D4052	0.855

### Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2020

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved