



Mobil Super 3000™ XE4 5W-30

Mobil Passenger Vehicle Lube , Colombia

Mobil passenger-vehicle-lube

Product Description

Mobil Super™ 3000 engine oil series are full synthetic oils engineered to deliver outstanding protection.

Mobil Super™ 3000 XE4 5W-30 is a high performance, low ash engine oil designed to help prolong engine life and maintain the efficiency of the exhaust emission reduction systems in both diesel and gasoline powered passenger cars, light commercial vehicles and vans.

This product is recommended for use in Mercedes vehicles and a wide range of European cars and light-duty commercial vehicles with oil specifications built on the ACEA C3 and/or API SP industry baseline.

Features and Benefits

Mobil Super™ 3000 XE4 5W-30 helps to maintain the efficiency of the exhaust emission reduction systems in both diesel and gasoline vehicles.

- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Long term engine protection from wear and sludge and deposit build-up
- Suitable for use in both gasoline and diesel engine passenger car and light commercial vehicles

Applications

Mobil Super™ 3000 XE4 5W-30 has been developed to meet the latest specifications for engine oils required by major car manufacturers and is compatible with the latest Gasoline and Diesel Particulate Filters and catalytic converters.

Mobil Super™ 3000 XE4 5W-30 is specially recommended by ExxonMobil for use in:

- Mercedes passenger cars and light commercial vehicles or vans. This motor oil is also recommended for many light commercial vehicles or vans requiring ACEA C3 and/or API SP
- Gasoline and Diesel with Diesel Particulate Filters (DPF) & Catalytic Convertors.
- Normal to occasionally severe operating conditions including city driving conditions.

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product has the following approvals:

RENAULT RN0700

RENAULT RN0710

MB-Approval 229.51

MB-Approval 229.52

BMW Longlife 04

This product meets or exceeds the requirements of:

ACEA C3

API SN

API SN PLUS

API SP

API SP Resource Conserving

ILSAC GF-6A

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	12.2
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	61.0
Ash, Sulfated, mass%, ASTM D874	0.73
Density @ 15 C, g/ml, ASTM D4052	0.85
Flash Point, Cleveland Open Cup, °C, ASTM D92	244
Pour Point, °C, ASTM D97	-42
Phosphorus, mass%, ASTM D4951	0.08

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise

12-2022

Organización Terpel S.A.

Address: Carrera 7 N° 75-51, Bogotá – Colombia

Phone: (57) 1 3267878

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon Mobil  

© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved