



Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty

Mobil Commercial Vehicle Lube , Costa Rica

Mobil commercial-vehicle-lube

Product Description

Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is a high performance diesel engine oil that provides proven engine protection of diesel engines operating in off-highway severe service applications. Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty is recommended by ExxonMobil for use in a wide range of heavy applications and operating environments found in the trucking, mining, construction, quarrying, and agricultural industries.

Features and Benefits

The technology in Mobil Delvac Legend™ CH-4 15W-40 Heavy Duty delivers excellent performance in both modern diesel engines as well as older models. Provides up to an average of 30% more viscosity control<sup>1</sup>.

| Features   | Advantages and Potential Benefits           |
|--|---|
| Provides up to an average of 40% more valve train wear protection <sup>1</sup> | Longer engine life                          |
| TBN reserve  | Deposit control                             |
| Stay-in-grade shear stability  | Reduced oil consumption and wear protection |
| Excellent detergency/dispersancy   | Clean engines and long engine life          |
| Thermal and oxidation stability  | Controls sludge build-up and deposits       |

1. Compared to API CH-4 standard. Based on Sequence IIIF and RFWT engine test.

Applications

Recommended by ExxonMobil for use in:

- Naturally aspirated and turbo-charged diesel powered equipment from Chinese, European, Japanese, and American manufacturers.
- On-highway light and heavy-duty trucking.
- Off-highway industries including: construction, mining, quarrying, and agriculture.

Specifications and Approvals

| This product has the following approvals:          |
|--|
| MB-Approval 228.3                                  |
| MTU Oil Category 2                                 |
| This product meets or exceeds the requirements of: |
| API CH-4   |
| API SJ   |

|  |
|--|
| This product meets or exceeds the requirements of: |
| Cummins CES 20076                                  |

Properties and Specifications

| Property                                      |            |
|---|------------|
| Grade   | SAE 15W-40 |
| Viscosity Index, ASTM D2270                   | 137        |
| Pour Point, °C, ASTM D97                      | -33        |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445  | 115.9      |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 15.21      |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 233        |
| Density @ 15 C, kg/l, ASTM D4052              | 0.87       |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

ExxonMobil

Exxon

Mobil

Esso

Xtreme

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved