



## Mobil Delvac Light Commercial Vehicle F 5W-30

Mobil Commercial Vehicle Lube , Cyprus

Synthetic Light Commercial Vehicle Engine Oil

### Product Description

Mobil Delvac™ Light Commercial Vehicle F 5W-30 is a synthetic engine oil that provides long engine life and excellent engine protection against sludge & wear.

Mobil Delvac™ Light Commercial Vehicle F 5W-30 provides excellent lubrication of diesel and gasoline engines operating in severe driving conditions typically encountered in city operations. This product is recommended by ExxonMobil for European engines for use in a wide range of light-duty commercial vehicles like Ford but also vans requiring to meet the requirements of ACEA A1/B1 or A5/B5.

### Features and Benefits

Mobil Delvac™ Light Commercial Vehicle F 5W-30 is formulated from high performance base oils and a superior balanced additive system to provide optimum engine performance in recent diesel and gasoline engines as well as older models. Key benefits include:

| Features   | Advantages and Potential Benefits   |
|--|---|
| Increased thermal and oxidation stability  | Help to reduced sludge build-up, deposits, and long oil and engine life         |
| Enhanced wear protection   | Helps towards long component and engine life                                    |
| Advanced piston deposit control  | Helps to keep engines clean with reduced maintenance costs and long engine life |
| Advanced soot handling to control viscosity increase, sludge build up, and filter pressure | Helps to enhance engine protection for long engine life                         |
| Enhanced low temperature pumpability   | Fast start up with reduced wear operating in low temperature climates           |
| Stayed in viscosity grade  | Helps to maintain fuel economy  |

### Applications

ExxonMobil recommends Mobil Delvac™ Light Commercial Vehicle F 5W-30 for demanding driving conditions:

- Ford Light Commercial Vehicles for engines requiring WSS-M2C913-D and also where WSS-M2C913-C is recommended.
- Light Commercial Vehicles requiring ACEA A5/B5 or A1/B1
- Normal to occasionally severe operating conditions (including city driving conditions)

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

### Specifications and Approvals

|   |
|---|
| <b>This product meets or exceeds the requirements of:</b> |
| API SL  |

**This product meets or exceeds the requirements of:**

Ford WSS-M2C913-C

Ford WSS-M2C913-D

API SN Engine Test Requirements

**Properties and Specifications**

| Property   |           |
|--|-----------|
| Grade  | SAE 5W-30 |
| Kinematic Viscosity @ 40 C, mm <sup>2</sup> /s, ASTM D445  | 52        |
| Kinematic Viscosity @ 100 C, mm <sup>2</sup> /s, ASTM D445 | 9.6       |
| Ash, Sulfated, mass%, ASTM D874                            | 1.08      |
| Total Base Number, mgKOH/g, ASTM D2896                     | 11        |
| Flash Point, °C, ASTM D92                                  | 222       |
| Density @ 15 C, g/ml, ASTM D4052                           | 0.85      |
| Pour Point, °C, ASTM D97                                   | -39       |

**Health and safety**

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

**ExxonMobil**

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved