



Mobil 1™ 0W-20
Mobil Passenger Vehicle Lube , Cyprus
Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ is the world's leading synthetic engine oil brand delivering our ultimate performance and protection.

Mobil 1™ 0W-20 is an advanced full synthetic engine oil designed to help deliver outstanding engine protection and enhanced fuel economy. Mobil 1 0W-20 exceeds the requirements of various vehicle manufacturers and industry standards. Mobil 1 0W-20 is specially designed for American and Asian design gasoline engines found in modern hybrid vehicles. Mobil 1 0W-20 helps to keep your engine running like new by providing exceptional wear protection, cleaning power and performance and outperforms our conventional oils.

Features and Benefits

Mobil 1 0W-20 is engineered with a proprietary blend of high performance synthetic basestocks fortified with a precisely balanced component additive system. Its viscosity, advanced full synthetic formulation helps to increase engine efficiency and improve fuel economy. Mobil 1 0W-20 provides the high-temperature protection of higher viscosity oils while offering the best fuel economy in the Mobil 1 line. Key features and potential benefits include:

| Features | Advantages and Potential Benefits |
|--|--|
| Low viscosity, advanced full synthetic formula | Helps improve fuel economy when switching from higher viscosity oils. Actual savings are dependent upon vehicle/engine outside temperature, driving conditions and your current engine oil viscosity |
| Outstanding thermal and oxidation stability | Helps to reduce oil aging resulting in long lasting protection |
| Outstanding low temperature capabilities | Quick cold weather starting and fast protection helps to extend engine life |
| Precisely balanced additive component system | Excellent overall lubrication and wear protection performance helps provide low-speed pre-ignition (LSPI) and timing chain protection while keeping your engine clean. |

Applications

- Mobil 1 0W-20 is designed for modern high efficiency turbocharged gasoline engines of American design from General Motors, Ford, Chrysler and Fiat gasoline engines, as well as for Japanese and Korean vehicles that specifically call for a SAE 0W-20 viscosity grade and any of the specifications the oil supports. Mobil 1 0W-20 satisfies the requirements of hybrid applications for which it is highly recommended.
- Mobil 1 0W-20 has been field tested in a Toyota Prius taxi vehicle operated day-in day-out up to 160,000 km. Periodical oil condition monitoring and engine inspection demonstrated that Mobil 1 0W-20 presents an excellent resistance to thermal oxidation and shearing, leading to excellent protection of the engine against wear deposit build-up despite the strenuous operating conditions and the accumulation of numerous stop-and-go events.
 - Mobil 1 0W-20 meets or exceeds the requirements of 'API SP Resource Conserving' industry standard therefore contributing to engine fuel efficiency and helping to address LSPI (Low Speed Pre-Ignition) making it a preferred choice for downsized direct injection turbocharged gasoline engines.
 - Mobil 1 0W-20 can be used for many driving styles and conditions, from mild to severe, where a SAE 0W-20 or SAE 5W-20 engine oil is recommended. It is not suitable for vehicle engines designed to operate with higher viscosity engine oils. Mobil 1 0W-20 is not recommended for 2-Cycle or aviation engines, unless specifically approved by the manufacturer.

Owner's manual should be consulted for recommended viscosity grades and specification.

Specifications and Approvals

| |
|--|
| This product has the following approvals: |
| GM dexos1:GEN3 Licensed |

| |
|---|
| This product is recommended for use in applications requiring: |
| Ford WSS-M2C947-A |
| Ford WSS-M2C947-B1 |
| GM 6094M |
| FIAT 9.55535-CR1 |

| |
|---|
| This product meets or exceeds the requirements of: |
| API SJ |
| API SL |
| API SM |
| API SN |
| API SN PLUS |
| API SN Resource Conserving |
| API SN PLUS RESOURCE CONSERVING |
| API SP |
| API SP Resource Conserving |
| ILSAC GF-6A |
| ACEA C5 |
| Chrysler MS-6395 |
| FORD WSS-M2C962-A1 |

Properties and Specifications

| Property | |
|---|-----------|
| Grade | SAE 0W-20 |
| Pour Point, °C, ASTM D97 | -48 |
| Phosphorus, mass%, ASTM D4951 | 0.08 |
| Ash, Sulfated, mass%, ASTM D874 | 0.9 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 235 |

| Property | |
|---|-------|
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 45 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 2.6 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 8.4 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.845 |
| Viscosity Index, ASTM D2270 | 162 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.as>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect pro performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without nc All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intende override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entit

ExxonMobil

Exxon

Mobil

Esso

XTO

© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved