



Mobil 1™ FS X2 5W-50

Mobil Passenger Vehicle Lube , Cyprus

Advanced Full Synthetic Motor Oil

Product Description

Mobil 1™ FS x2 5W-50 advanced performance synthetic engine oil is a select member of Mobil 1™, the world's leading synthetic engine oil brand delivering our ultimate performance and protection.

Mobil 1 FS x2 5W-50 is engineered to deliver excellent all-round protection for engines operating in tough conditions. It is suitable for high performance and motorsport applications requiring high viscosity engine oils, and addresses the specific demands of older vehicles even above 100,000 km.

Racing or normal driving, Mobil 1 FS x2 5W-50 helps to provide heavy-duty engine performance and protection for an outstanding driving experience. Mobil 1 keeps your engine running like new!

Features and Benefits

Mobil 1 FS x2 5W-50 combines a proprietary blend of high performance synthetic base stocks fortified with a precisely balanced component system providing a reinforced protective oil film at high temperature while still ensuring superb oil flow properties at lower temperatures. Its full SAPS additive system contributes as well to exceptional cleaning power, engine wear protection and lubrication up to 20,000 km maximum oil drain interval.

- Excellent protection for your engine by helping to prevent the buildup of harmful deposits.
- Enhanced cleaning technology for cars with higher mileage (100 000km +).
- Improved protection against variable fuel quality*.
- Low temperature viscosity grade (SAE 5W) to help protect your engine during cold start-up.
- High temperature viscosity grade (SAE 50) to help build a strong lubricating oil film to protect against wear, and to help reduce oil consumption or leaks in high-mileage engines.
- Helps prevent Low Speed Pre-Ignition (LSPI) occurrences and timing chain wear in gasoline direct injection turbocharged engines (GTDI).

* Performance compared in industry standard tests, which use fuels designed to promote sludge formation.

Applications

Mobil 1 FS x2 5W-50 is suitable for the latest generation high powered vehicles with gasoline and Diesel engines (without Particulate Filter), turbo-charged or naturally aspirated, as well for the older gasoline engines calling for high viscosity engine oils meeting prior API standards.

- It is well suited for motorsport applications and extreme driving conditions (high temperatures and loads, car towing...).
- Mobil 1 FS x2 5W-50 helps also provide the extra protection that older vehicles and vehicles with higher mileage (> 100 000 km) can demand.

Always consult your owner's manual to check the recommended viscosity grade, specifications and drain interval for your particular vehicle.

Specifications and Approvals

This product has the following approvals:

MB-Approval 229.3

| |
|--|
| This product has the following approvals: |
| Porsche A40 |

| |
|---|
| This product is recommended for use in applications requiring: |
| API CF |
| FIAT 9.55535-M2 |

| |
|---|
| This product meets or exceeds the requirements of: |
| API SJ |
| API SL |
| API SM |
| API SN |
| API SN PLUS |
| API SP |
| ACEA A3/B3 |
| ACEA A3/B4 |
| LEXUS LFA Service Fill |

Properties and Specifications

| Property | |
|---|-----------|
| Grade | SAE 5W-50 |
| Kinematic Viscosity @ 100 C, mm2/s, ASTM D445 | 18.6 |
| Kinematic Viscosity @ 40 C, mm2/s, ASTM D445 | 112 |
| Viscosity Index, ASTM D2270 | 185 |
| Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683 | 4.3 |
| Pour Point, °C, ASTM D97 | -39 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 225 |
| Total Base Number, mgKOH/g, ASTM D2896 | 13 |
| Density @ 15.6 C, g/ml, ASTM D4052 | 0.841 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil



© Copyright 2003-2024 Exxon Mobil Corporation. All Rights Reserved