



Mobil DTE™ Hydraulic Zinc Free Series

Mobil Industrial , Czech Republic

Hydraulic Oil

Product Description

Mobil DTE™ Hydraulic Zinc Free Series oils are superior hydraulic oils specifically designed to meet the needs of modern, high pressure, industrial and mobile equipment hydraulic systems. They are formulated from high quality base stocks and specially selected zinc free additives. This unique additive system was developed to give exceptional protection due to excellent anti-wear performance in severe hydraulic applications.

The Mobil DTE™ Hydraulic Zinc Free oils exhibit excellent oxidation and thermal stability properties which can help to provide extended oil and filter life, as well as optimum equipment protection, thereby reducing both maintenance and product disposal costs. They are designed to work with systems operating under moderate to severe conditions where high levels of anti-wear and film strength protection are needed.

Features and Benefits

The Mobil DTE™ Hydraulic Zinc Free hydraulic oils exhibit excellent oxidation resistance and thermal stability characteristics that can lead to extension of oil and filter change intervals and help to provide clean systems and trouble-free operation. Their high level of anti-wear properties and excellent film strength characteristics can lead to equipment performance that can not only result in fewer breakdowns, but also can help to enhance productivity. Their outstanding demulsibility permits the oils to work well in systems contaminated with small amounts of water, and readily separate large amounts of water.

Features	Advantages and Potential Benefits
Thermal and Oxidation Stability	Provides long oil and equipment life
Anti-wear Properties	Helps reduce wear and protects pumps and components for extended equipment life
Excellent Demulsibility Characteristics	Protects systems where small quantities of moisture are present
Multi Metal Compatibility	Helps ensure excellent performance and protection with a wide variety of component metallurgy
Meets a Wide Range of Equipment Requirements	Minimizes inventory requirements

Applications

- Systems employing multi-metal designs in pumps and other system components
- Applications where cross-contamination of hydraulic fluids and coolants can occur
- High pressure vane, piston and gear pumps
- Where small amounts of water are unavoidable
- In systems containing gears and bearings
- Systems requiring a high degree of load-carrying capability and anti-wear protection

Specifications and Approvals

This product has the following approvals:	MOBIL HYDRAULIC FREE 22	DTE ZINC	MOBIL HYDRAULIC FREE 32	DTE ZINC	MOBIL HYDRAULIC FREE 46	DTE ZINC	MOBIL HYDRAULIC FREE 68	DTE ZINC	MOBIL HYDRAULIC ZINC FREE 100

This product has the following approvals:	MOBIL HYDRAULIC FREE 22	DTE ZINC	MOBIL HYDRAULIC FREE 32	DTE ZINC	MOBIL HYDRAULIC FREE 46	DTE ZINC	MOBIL HYDRAULIC FREE 68	DTE ZINC	MOBIL HYDRAULIC ZINC FREE 100	DTE ZINC
Bosch Rexroth Fluid Rating List 90245			X		X		X			
Denison HF-0			X		X		X			
Denison HF-1			X		X		X			
Denison HF-2			X		X		X			
Eaton E-FDGN-TB002-E			X		X		X			

This product is recommended for use in applications requiring:					
Fives Cincinnati P-68			X		
Fives Cincinnati P-69				X	
Fives Cincinnati P-70			X		

This product meets or exceeds the requirements of:					
ASTM D6158 (Class HMHP)	X	X	X	X	X
China GB 11118.1-2011, L-HM(General)	X	X	X	X	X
China GB 11118.1-2011, L-HM(HP)		X	X	X	X
DIN 51524-2:2017-06	X	X	X	X	X
ISO L-HM (ISO 11158:2009)	X	X	X	X	X
JCMAS HK VG32		X			
JCMAS HK VG46			X		

Properties and Specifications

Property	MOBIL HYDRAULIC FREE 22	DTE ZINC	MOBIL HYDRAULIC FREE 32	DTE ZINC	MOBIL HYDRAULIC FREE 46	DTE ZINC	MOBIL HYDRAULIC FREE 68	DTE ZINC	MOBIL HYDRAULIC ZINC FREE 100	DTE ZINC
Grade	ISO 22		ISO 32		ISO 46		ISO 68		ISO 100	
Density @ 15.6 C, kg/l, ASTM D4052	0.859		0.857		0.864		0.871		0.866	
Flash Point, Cleveland Open Cup, °C, ASTM D92	208		224		232		242		270	

Property	MOBIL HYDRAULIC FREE 22	DTE ZINC	MOBIL HYDRAULIC FREE 32	DTE ZINC	MOBIL HYDRAULIC FREE 46	DTE ZINC	MOBIL HYDRAULIC FREE 68	DTE ZINC	MOBIL HYDRAULIC FREE 100	DTE ZINC
Foam, Sequence I, Stability, ml, ASTM D892	0		0		0		0		0	
Foam, Sequence I, Tendency, ml, ASTM D892	0		0		0		0		0	
Foam, Sequence II, Stability, ml, ASTM D892	0		0		0		0		0	
Foam, Sequence II, Tendency, ml, ASTM D892	0		0		0		0		0	
Foam, Sequence III, Stability, ml, ASTM D892	0		0		0		0		0	
Foam, Sequence III, Tendency, ml, ASTM D892	10		0		0		0		0	
Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445	4.5		5.66		7.01		8.84		11.77	
Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445	22.6		32.72		46.26		68.33		99.86	
Rust Prevention, Procedure B, Rating, ASTM D665	PASS		PASS		PASS		PASS		PASS	
Viscosity Index, ASTM D2270	115		112		108		102		107	

Health and Safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

12-2022

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil



© Copyright 2003-2023 Exxon Mobil Corporation. All Rights Reserved